Product data sheet Characteristics

D224NRB

Safety switch, general duty, fusible, 200A, 2 poles, 60 hp, 120 VAC, NEMA 3R, bolt-on provision, neutral factory installed

Product availability: Stock - Normally stocked in distribution facility

SQUARE D



Price*: 1,200.00 USD



Main

Product	Single Throw Safety Switch	
Duty Rating	General duty	
Device application	Residential	:
Disconnect Type	Fusible disconnect switch	
Factory Installed Neutral	Neutral (factory installed)	
Phase	3 phase	 :
Number of Poles	2	
Current Rating	200 A	
Voltage Rating	240 V AC	
Enclosure Rating NEMA	NEMA 3R	
Maximum Horse Power Rating	15 hp 240 V at AC 60 Hz for 1 phase conforming to NEC 240.6 25 hp 240 V at AC 60 Hz for 3 phase conforming to NEC 240.6 60 hp 240 V at AC 60 Hz for 3 phase conforming to NEC 430.52	

Complementary

Complementary		· ·
Short Circuit Current Rating	100 kA maximum depending on fuse H, K or R	
Fuse type	H, K or R	
Mounting Type	Surface	
Electrical Connection	Lugs	
Wiring configuration	3-wire	
Wire Size	AWG 6250 kcmil aluminium/copper	
Tightening torque	275 lbf.in (31.07 N.m) (AWG 6250 kcmil)	
Depth	8.5 in (215.90 mm)	·
Width	19 in (482.60 mm)	ı

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Height	29.25 in (742.95 mm)
Net Weight	53.51 lb(US) (24.27 kg)

Environment

0 45 4	
Certifications UL listed file E2875	

Ordering and shipping details

Category	00106 - D & DU SW,NEMA3R, 30-200A	
Discount Schedule	DE1A	
GTIN	00785901460763	
Nbr. of units in pkg.	1	
Package weight(Lbs)	42.70 lb(US) (19.368 kg)	
Returnability	Yes	
Country of origin	US	

Packing Units

r acking chilis	
Unit Type of Package 1	PCE
Package 1 Height	8.50 in (21.59 cm)
Package 1 width	19.50 in (49.53 cm)
Package 1 Length	30.50 in (77.47 cm)
Unit Type of Package 2	PAL
Number of Units in Package 2	15
Package 2 Weight	670.00 lb(US) (303.907 kg)
Package 2 Height	45.00 in (114.3 cm)
Package 2 width	40.00 in (101.6 cm)
Package 2 Length	48.00 in (121.92 cm)

Offer Sustainability

Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, whic is known to the State of California to cause cancer and birth defects or other reproductive harm. F more information go to www.P65Warnings.ca.gov	
REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)	
Environmental Disclosure	Product Environmental Profile	
PVC free	Yes	

Contractual warranty

Warranty	18 months	