

## Product data sheet

### Characteristics

# LC1D25G7

IEC contactor, TeSys D, nonreversing, 25A, 15HP at 480VAC, up to 100kA SCCR, 3 phase, 3 NO, 120VAC 50/60Hz coil, open

Product availability : Stock - Normally stocked in distribution facility



Price\* : 151.00 USD



### Main

|                                |                                                                                                                                                                                                                                                                              |
|--------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Range                          | TeSys                                                                                                                                                                                                                                                                        |
| Product name                   | TeSys D                                                                                                                                                                                                                                                                      |
| Product or component type      | Contactor                                                                                                                                                                                                                                                                    |
| Device short name              | LC1D                                                                                                                                                                                                                                                                         |
| Contactor application          | Motor control<br>Resistive load                                                                                                                                                                                                                                              |
| Utilisation category           | AC-3<br>AC-4<br>AC-1                                                                                                                                                                                                                                                         |
| Poles description              | 3P                                                                                                                                                                                                                                                                           |
| Power pole contact composition | 3 NO                                                                                                                                                                                                                                                                         |
| [Ue] rated operational voltage | Power circuit <= 690 V AC 25...400 Hz<br>Power circuit <= 300 V DC                                                                                                                                                                                                           |
| [Ie] rated operational current | 25 A 140 °F (60 °C)) <= 440 V AC AC-3 power circuit<br>40 A 140 °F (60 °C)) <= 440 V AC AC-1 power circuit                                                                                                                                                                   |
| Motor power kW                 | 5.5 kW 220...230 V AC 50/60 Hz AC-3)<br>11 kW 380...400 V AC 50/60 Hz AC-3)<br>11 kW 415...440 V AC 50/60 Hz AC-3)<br>15 kW 500 V AC 50/60 Hz AC-3)<br>15 kW 660...690 V AC 50/60 Hz AC-3)<br>5.5 kW 400 V AC 50/60 Hz AC-4)                                                 |
| Motor power HP (UL / CSA)      | 3 hp 230/240 V at AC 50/60 Hz for 1 phase<br>2 hp 115 V at AC 50/60 Hz for 1 phase<br>7.5 hp 230/240 V at AC 50/60 Hz for 3 phase<br>15 hp 460/480 V at AC 50/60 Hz for 3 phase<br>20 hp 575/600 V at AC 50/60 Hz for 3 phase<br>7.5 hp 200/208 V at AC 50/60 Hz for 3 phase |
| Control circuit type           | AC 50/60 Hz                                                                                                                                                                                                                                                                  |

\* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Jul 29, 2021

|                                             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|---------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| [Uc] control circuit voltage                | 120 V AC 50/60 Hz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Auxiliary contact composition               | 1 NO + 1 NC                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| [Uimp] rated impulse withstand voltage      | 6 kV IEC 60947                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Overvoltage category                        | III                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| [Ith] conventional free air thermal current | 10 A 140 °F (60 °C) signalling circuit<br>40 A 140 °F (60 °C) power circuit                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Irms rated making capacity                  | 140 A AC signalling circuit IEC 60947-5-1<br>250 A DC signalling circuit IEC 60947-5-1<br>450 A 440 V power circuit IEC 60947                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Rated breaking capacity                     | 450 A 440 V power circuit IEC 60947                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| [Icw] rated short-time withstand current    | 240 A 104 °F (40 °C) - 10 s power circuit<br>380 A 104 °F (40 °C) - 1 s power circuit<br>50 A 104 °F (40 °C) - 10 min power circuit<br>120 A 104 °F (40 °C) - 1 min power circuit<br>100 A - 1 s signalling circuit<br>120 A - 500 ms signalling circuit<br>140 A - 100 ms signalling circuit                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Associated fuse rating                      | 10 A gG signalling circuit IEC 60947-5-1<br>63 A gG ≤ 690 V type 1 power circuit<br>40 A gG ≤ 690 V type 2 power circuit                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Average impedance                           | 2 mOhm - Ith 40 A 50 Hz power circuit                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| [Ui] rated insulation voltage               | Power circuit 690 V IEC 60947-4-1<br>Power circuit 600 V CSA<br>Power circuit 600 V UL<br>Signalling circuit 690 V IEC 60947-1<br>Signalling circuit 600 V CSA<br>Signalling circuit 600 V UL                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Electrical durability                       | 1.65 Mcycles 25 A AC-3 ≤ 440 V<br>1.4 Mcycles 40 A AC-1 ≤ 440 V                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Power dissipation per pole                  | 3.2 W AC-1<br>1.25 W AC-3                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Front cover                                 | With                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Mounting support                            | Rail<br>Plate                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Standards                                   | CSA C22.2 No 14<br>EN 60947-4-1<br>EN 60947-5-1<br>IEC 60947-4-1<br>IEC 60947-5-1<br>UL 508                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Product certifications                      | UL<br>BV<br>RINA<br>GOST<br>DNV<br>LROS (Lloyds register of shipping)<br>CCC<br>GL<br>CSA                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Connections - terminals                     | Control circuit screw clamp terminals 1 0.00...0.01 in <sup>2</sup> (1...4 mm <sup>2</sup> )flexible without cable end<br>Control circuit screw clamp terminals 2 0.00...0.01 in <sup>2</sup> (1...4 mm <sup>2</sup> )flexible without cable end<br>Control circuit screw clamp terminals 1 0.00...0.01 in <sup>2</sup> (1...4 mm <sup>2</sup> )flexible with cable end<br>Control circuit screw clamp terminals 2 0.00...0.00 in <sup>2</sup> (1...2.5 mm <sup>2</sup> )flexible with cable end<br>Control circuit screw clamp terminals 1 0.00...0.01 in <sup>2</sup> (1...4 mm <sup>2</sup> )solid without cable end<br>Control circuit screw clamp terminals 2 0.00...0.01 in <sup>2</sup> (1...4 mm <sup>2</sup> )solid without cable end<br>Power circuit screw clamp terminals 1 0.00...0.02 in <sup>2</sup> (2.5...10 mm <sup>2</sup> )flexible without cable end<br>Power circuit screw clamp terminals 2 0.00...0.02 in <sup>2</sup> (2.5...10 mm <sup>2</sup> )flexible without cable end<br>Power circuit screw clamp terminals 1 0.00...0.02 in <sup>2</sup> (1...10 mm <sup>2</sup> )flexible with cable end<br>Power circuit screw clamp terminals 2 0.00...0.01 in <sup>2</sup> (1.5...6 mm <sup>2</sup> )flexible with cable end<br>Power circuit screw clamp terminals 1 0.00...0.02 in <sup>2</sup> (1.5...10 mm <sup>2</sup> )solid without cable end<br>Power circuit screw clamp terminals 2 0.00...0.02 in <sup>2</sup> (2.5...10 mm <sup>2</sup> )solid without cable end |
| Tightening torque                           | Control circuit 15.05 lbf.in (1.7 N.m) screw clamp terminals flat Ø 6 mm<br>Control circuit 15.05 lbf.in (1.7 N.m) screw clamp terminals Philips No 2<br>Power circuit 22.13 lbf.in (2.5 N.m) screw clamp terminals flat Ø 6 mm<br>Power circuit 22.13 lbf.in (2.5 N.m) screw clamp terminals Philips No 2                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Operating time                              | 12...22 ms closing<br>4...19 ms opening                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |

|                          |                                                                                                                                          |
|--------------------------|------------------------------------------------------------------------------------------------------------------------------------------|
| Safety reliability level | B10d = 1369863 cycles contactor with nominal load EN/ISO 13849-1<br>B10d = 20000000 cycles contactor with mechanical load EN/ISO 13849-1 |
| Mechanical durability    | 15 Mcycles                                                                                                                               |
| Maximum operating rate   | 3600 cyc/h 60 °C                                                                                                                         |

## Complementary

|                                 |                                                                                                                                                                                                                                                               |
|---------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Coil technology                 | Without built-in suppressor module                                                                                                                                                                                                                            |
| Control circuit voltage limits  | 0.3...0.6 Uc -40...158 °F (-40...70 °C) drop-out AC 50/60 Hz<br>0.8...1.1 Uc -40...140 °F (-40...60 °C) operational AC 50 Hz<br>0.85...1.1 Uc -40...140 °F (-40...60 °C) operational AC 60 Hz<br>1...1.1 Uc 140...158 °F (60...70 °C) operational AC 50/60 Hz |
| Inrush power in VA              | 70 VA 60 Hz 0.75 68 °F (20 °C))<br>70 VA 50 Hz 0.75 68 °F (20 °C))                                                                                                                                                                                            |
| Hold-in power consumption in VA | 7.5 VA 60 Hz 0.3 68 °F (20 °C))<br>7 VA 50 Hz 0.3 68 °F (20 °C))                                                                                                                                                                                              |
| Heat dissipation                | 2...3 W 50/60 Hz                                                                                                                                                                                                                                              |
| Auxiliary contacts type         | type mechanically linked 1 NO + 1 NC conforming to IEC 60947-5-1<br>type mirror contact 1 NC conforming to IEC 60947-4-1                                                                                                                                      |
| Signalling circuit frequency    | 25...400 Hz                                                                                                                                                                                                                                                   |
| Minimum switching current       | 5 mA signalling circuit                                                                                                                                                                                                                                       |
| Minimum switching voltage       | 17 V signalling circuit                                                                                                                                                                                                                                       |
| Non-overlap time                | 1.5 ms on de-energisation between NC and NO contact<br>1.5 ms on energisation between NC and NO contact                                                                                                                                                       |
| Insulation resistance           | > 10 MOhm for signalling circuit                                                                                                                                                                                                                              |

## Environment

|                                       |                                                                                                                                                                                 |
|---------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| IP degree of protection               | IP20 front face conforming to IEC 60529                                                                                                                                         |
| Protective treatment                  | TH conforming to IEC 60068-2-30                                                                                                                                                 |
| Pollution degree                      | 3                                                                                                                                                                               |
| Ambient air temperature for operation | -40...140 °F (-40...60 °C)<br>140...158 °F (60...70 °C) with derating                                                                                                           |
| Ambient air temperature for storage   | -76...176 °F (-60...80 °C)                                                                                                                                                      |
| Operating altitude                    | 0...3000 m                                                                                                                                                                      |
| Fire resistance                       | 1562 °F (850 °C) IEC 60695-2-1                                                                                                                                                  |
| Flame retardance                      | V1 conforming to UL 94                                                                                                                                                          |
| Mechanical robustness                 | Vibrations contactor open: 2 Gn, 5...300 Hz<br>Vibrations contactor closed 4 Gn, 5...300 Hz<br>Shocks contactor closed 15 Gn for 11 ms<br>Shocks contactor open: 8 Gn for 11 ms |
| Height                                | 3.35 in (85 mm)                                                                                                                                                                 |
| Width                                 | 1.77 in (45 mm)                                                                                                                                                                 |
| Depth                                 | 3.62 in (92 mm)                                                                                                                                                                 |
| Net Weight                            | 0.82 lb(US) (0.37 kg)                                                                                                                                                           |

## Ordering and shipping details

|                       |                                      |
|-----------------------|--------------------------------------|
| Category              | 22354 - CTR, TESYS D, OPEN, 9-38A AC |
| Discount Schedule     | I12                                  |
| GTIN                  | 03389110349733                       |
| Nbr. of units in pkg. | 1                                    |
| Package weight(Lbs)   | 14.49 oz (410.75 g)                  |
| Returnability         | Yes                                  |
| Country of origin     | ID                                   |

## Packing Units

|                        |     |
|------------------------|-----|
| Unit Type of Package 1 | PCE |
|------------------------|-----|

|                              |                           |
|------------------------------|---------------------------|
| Package 1 Height             | 1.97 in (5 cm)            |
| Package 1 width              | 3.74 in (9.5 cm)          |
| Package 1 Length             | 4.53 in (11.5 cm)         |
| Unit Type of Package 2       | S02                       |
| Number of Units in Package 2 | 20                        |
| Package 2 Weight             | 18.80 lb(US) (8.526 kg)   |
| Package 2 Height             | 5.91 in (15 cm)           |
| Package 2 width              | 11.81 in (30 cm)          |
| Package 2 Length             | 15.75 in (40 cm)          |
| Unit Type of Package 3       | P06                       |
| Number of Units in Package 3 | 320                       |
| Package 3 Weight             | 326.15 lb(US) (147.94 kg) |
| Package 3 Height             | 30.31 in (77 cm)          |
| Package 3 width              | 31.50 in (80 cm)          |
| Package 3 Length             | 23.62 in (60 cm)          |

## Offer Sustainability

|                            |                                                                                                                                                                                                                                                           |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                                                                                                                                                                                     |
| California proposition 65  | WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| REACH Regulation           | <a href="#">REACH Declaration</a>                                                                                                                                                                                                                         |
| REACH free of SVHC         | Yes                                                                                                                                                                                                                                                       |
| EU RoHS Directive          | Compliant<br><a href="#">EU RoHS Declaration</a>                                                                                                                                                                                                          |
| Toxic heavy metal free     | Yes                                                                                                                                                                                                                                                       |
| Mercury free               | Yes                                                                                                                                                                                                                                                       |
| RoHS exemption information | <a href="#">Yes</a>                                                                                                                                                                                                                                       |
| China RoHS Regulation      | <a href="#">China RoHS declaration</a><br>Pro-active China RoHS declaration (out of China RoHS legal scope)                                                                                                                                               |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>                                                                                                                                                                                                             |
| Circularity Profile        | <a href="#">End of Life Information</a>                                                                                                                                                                                                                   |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.                                                                                                                              |
| PVC free                   | Yes                                                                                                                                                                                                                                                       |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Electrical Clearance/Wire Bending Space

Minimum to wall or barrier to ensure adequate wire bending space to lug surface when the maximum wire size is used. REF. NEC 430-10

1.50 [38.1]

2.20 [55.9]

1.57 [39.9]

.67 [17]

.47 [11.9]

.39 [9.9]

.71 [18]

1.89 [48]

1.97 [50]

2.37 [60.2]

3.31 [84.1]

1.57 [39.9]

.31 [7.9]

in.  
[mm]

Depth: LC1 D25 — 3.66 [93]  
Depth: LC1 D32 — 3.86 [98]