


MALE END VIEW



SPECIFICATIONS

CONTACT MATERIAL/PLATING	BRASS/GOLD
COUPLING NUT MATERIAL/PLATING	BRASS/NICKEL
RATED CURRENT [A]	4.0 A
RATED VOLTAGE [V]	250 V
MAXIMUM WIRE SIZE	18 AWG
CABLE GRIP RANGE	6–8mm
TEMPERATURE RATING	–40°C to +85°C (–40°F to +185°F)
PROTECTION CLASS	IEC IP67
WIRE TERMINATION	SCREW TERMINAL

41.8 [1.65]
ASSEMBLED HEIGHT
APPROX.

19.6 [0.77]
M12x1

54.0 [2.13]
REF.

20.0 [0.79]

KEY-WAY
ADJUSTABLE
BY 90°
INCREMENTS

8.0 [0.32] MAX
CABLE DIAMETER

18.0 [0.71]

ALL METAL SHIELDED FIELD WIREABLE CONNECTOR

RELATED DOCUMENTS

3RD ANGLE PROJECTION

THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.

1.

2.

3.

4.

DRFT

APVD

DATE 07/24/00

SCALE 1=1.0

DESCRIPTION

CMBS 8241-0

IDENTIFICATION NO.

U6111-0

REV

A

MATERIAL

SEE SPECIFICATIONS

FINISH

SEE SPECIFICATIONS

ALL DIMENSIONS DISPLAYED ON THIS DRAWING ARE FOR REFERENCE ONLY

CONTACT TURCK FOR MORE INFORMATION

UNIT OF MEASUREMENT

MILLIMETER [INCH]

DO NOT SCALE THIS DRAWING

3000 CAMPUS DRIVE
MINNEAPOLIS, MN 55441
1-800-544-7769
(763) 553-7300
(763) 553-0708 fax
www.turck.us

A	DRAWING RELEASE	JB	03/26/04	
REV	DESCRIPTION	BY	DATE	ECO. NO.