
REVISIONS REV. DESCRIPTION DATE APPROVED REDRAWN IN SW 6/15/2006

2



-7/8-16 UN2A 28 95 3.7 nom.

MATERIALS BODY: BLACK POLYAMIDE CONTACTS: GOLD PLATED COPPER ALLOY CABLE SEAL: NBR **INSERT: BLACK PVC NICKEL PLATED BRASS COUPLING: RATINGS** AMPS: 14AWG - 15A max 16AWG - 10A max 18AWG - 8A max 20-22AWG - 4A max **VOLTS: 600V MAX** SEAL: **IP67** CABLE RANGE: 14AWG - 22AWG 0.31" - 0.67" (8mm - 17mm) OD **APPROVALS** US: **UL LISTED CANADA: C-UL LISTED**

Voltage rating is 600V or the rating of the cable, whichever is less.

Connections made via screw terminal

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
MENCOM CORPORATION. ANY
REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF
MENCOM CORPORATION IS
PROHIBITED.

	UNLESS OTHERWISE SPECIFIED:		NAME	
	DIMENSIONS ARE IN INCHES AND [MM]	DRAWN	BEM	
		CHECKED		TITL
		ENG APPR.		
		MFG APPR.		
		Q.A.		
	MATERIAL	COMMENTS:		SIZI B
	1114511			ע
	DO NOT SCALE DRAWING			SCA

IIILL.	
SIZE DWG. NO.	REV
R MAINIC ANAP ENNY	Δ

MENCOM CORPORATION

MINC-4MP-FVVXSHEET 1 OF 1 CALE: 2:1 WEIGHT:

8