




# 1" MIN Power Series Cordsets

## 7 Conductor MIN Power Series Cordsets, 14/18AWG



Front Mount Receptacles | 1/2"-14 NPT Threads | Metric Threads | IP67 Rating

D  
MIN Power Receptacles

# of Poles	Male Faceview	Color Code	Wire AWG Rating	Mounting Threads	Male Receptacles	Female Receptacles
7	 1"-16UN2	<b>North American</b> 1. White/Black 2. <b>Black***</b> 3. <b>White***</b> 4. Red 5. Orange 6. Blue 7. Green/Yellow	<b>2 x 14 AWG</b> 300V, 12A or 9A  <b>5 x 18 AWG</b> 300V, 1A or 5A	1/2" NPT	MINH-7MR-**	MINH-7FR-**
				M20 x 1.5	MINH-7MR-**-M20	N/A


\*\* Length in meters. 0.3m leads are standard. Longer lead lengths are available, please consult the factory for part numbers.

\*\*\* Black and White wires are 14 AWG.


For 1/2" receptacles with lengths of 12" or shorter use the suffix "-G" to include lock nut and O-ring. (e.g. MINH-7MR-0.3M becomes MINH-7MR-0.3M-G)

For 1/2" receptacles with lengths of 15" or longer O-ring and lock nut are included.

1/2"-14 NPT Threads



M20 Threads



### Specifications:

Shell: Clear Anodized Aluminum  
Insulator: 105°C, Oil Resistant Yellow PVC  
Wire: 14 AWG: UL Style 1015, 600V  
18 AWG: UL Style 1007, 300V  
Contacts: Copper Alloy with Gold Plating  
O-Ring: NBR  
Temperature: -40°C to 105°C (-40°F to +221°F)