




15 and 20 Ampere, 125 Volts




HBL5362ITR




HBL5252



HBL5242



HBL5251



HBL2152

Dimensions in Inches (mm)



15A 125V
NEMA 5-15R
UL CSA
0.5 HP



20A 125V
NEMA 5-20R
UL CSA
1 HP

HBL® Extra Heavy Duty Tamper-Resistant Receptacles

Duplex



Flush, nylon face, Tamper-Resistant,
back and side wired.

Description	Color	Catalog Number	
	Black	HBL5262BKTR	HBL5362BKTR
	Blue	HBL5262BLTR	HBL5362BLTR
	Brown	HBL5262TR	HBL5362TR
	Gray	HBL5262GYTR	HBL5362GYTR
	Ivory	HBL5262ITR	HBL5362ITR
	Light Almond	HBL5262LATR	HBL5362LATR
	Red	HBL5262RTR	HBL5362RTR
	White	HBL5262WTR	HBL5362WTR

HBL® Extra Heavy Duty Compact Receptacles

Duplex

Flush, nylon face,
back and side wired.

Description	Color	Catalog Number	
	Black	HBL5252BK	HBL5352BK
	Blue	—	HBL5352BL
	Brown	HBL5252	HBL5352
	Gray	HBL5252GY	HBL5352GY
	Ivory	HBL5252I	HBL5352I
	Red	HBL5252R	HBL5352R
	White	HBL5252W	HBL5352W

On a 4 in. (101.6) round cover.

	Brown	HBL5253	—
--	-------	----------------	---

Flush, nylon face,
side wired only.

	Brown	HBL5242	HBL5342
	Gray	HBL5242GY	HBL5342GY
	Ivory	HBL5242I	HBL5342I
	White	HBL5242W	HBL5342W

Ring terminal connection.

	Brown	HBL5242RT	HBL5342RT
--	-------	------------------	------------------

Single

Flush, side wired only.

	Brown	HBL5251	—
	Ivory	HBL5251I	—

Panel mount 1.75 in.
(44.5) centers.

	Brown	HBL5258	HBL5358
	Ivory	HBL5258I	—

Style Line® Decorator*

Flush, nylon face,
back and side wired.

Description	Color	Catalog Number	
	Almond	HBL2152AL	HBL2162AL
	Black	HBL2152BK	HBL2162BK
	Brown	HBL2152	HBL2162
	Gray	HBL2152GY	HBL2162GY
	Ivory	HBL2152I	HBL2162I
	Office White	HBL2152OW	HBL2162OW
	White	HBL2152WA	HBL2162WA

Isolated ground^A.

	Gray	—	IG2162GY
	Orange	IG2152	IG2162

Note: ^ASee section N for additional information on isolated ground devices.

*Style Line Duplex devices are not Fed. Spec. Listed.

See page A-47 for accessories.

See section O for wallplates.