



7/8" MIN Series Size I Cordsets

2 & 3 Conductor MIN Series Size I Cordsets, 16AWG



Straight Female Cordsets | 600 Volt, 13 amps | 600 Volt, 10 amps | IP69 Rating



A

MIN Series Size I Cordsets

Connector Body Style	Part Number	Cables	Features	Color Code	Faceview
	MIN-2FP-*	Yellow PVC STOOW 2 X 16 AWG 600V, 13A -40°C to +105°C 9.4mm OD	Industry Standard PVC	North American 1. White 2. Black	 7/8"-16UN2
	MIN-3FP- (YELLOW) MIN-3FP- *-B (BLACK)	PVC STOOW 3 X 16 AWG 600V, 13A -40°C to +105°C 10mm OD	Industry Standard PVC	North American 1. Green/Yellow 2. Black 3. White	 7/8"-16UN2
	MINM-3FP-*	Yellow PVC STOOW With Foil Shield 3 X 16 AWG 600V, 13A -40°C to +105°C 10mm OD	Industry Standard PVC Foil Shield		
	MINP-3FP-*	Yellow PUR AWM 3 X 16 AWG 600V, 13A -40°C to +80°C 10mm OD	Oil and Cutting Fluid Resistant Cut Resistant PUR		
	MINW-3FP- (YELLOW) MINW-3FP- *-B (BLACK)	TPE SEOOW 3 X 16 AWG 600V, 13A -40°C to +80°C 10mm OD	Weld Slag Resistant TPE		
	MIN-3FP-*A	Yellow PVC STOOW 3 X 16 AWG 600V, 13A -40°C to +105°C 10mm OD	Industry Standard PVC	North American Auto Color Code 1. Green/Yellow 2. Red/Black 3. Red/White	 7/8"-16UN2

* Lengths in feet. Standard cable lengths are 3, 6, 12, 20, 30 & 50 feet. Consult factory for other lengths.

Standard coupling nut is nickel plated brass, for stainless steel coupling nut add a "SS" suffix. (e.g. MIN-3FP-3 becomes MIN-3FP-3-SS)

See Page A-33 for Armored Cordset options.