



# 7/8" MIN Series Size I Cordsets

## 2, 3 & 4 Conductor MIN Series Size I Cordsets, 16AWG









Right Angle Female Cordsets | 600 Volt, 13 amps | 600 Volt 10 amps | IP69 Rating



A

MIN Series Size I Cordsets

| Connector Body Style                                                                | Part Number                                           | Cables                                                                                                    | Features                                                   | Color Code                                                                                   | Faceview                                                                                            |
|-------------------------------------------------------------------------------------|-------------------------------------------------------|-----------------------------------------------------------------------------------------------------------|------------------------------------------------------------|----------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
|    | MIN-2FP-*-R                                           | Yellow PVC<br>STOOW<br><b>2 X 16 AWG</b><br>600V, 13A<br>-40°C to +105°C<br>9.5mm OD                      | Industry Standard PVC                                      | <b>North American</b><br>1. White<br>2. Black                                                | <br>7/8"-16UN2   |
|   | MIN-3FP-*-R<br>(YELLOW)<br>MIN-3FP-*-R-B<br>(BLACK)   | PVC<br>STOOW<br><b>3 X 16 AWG</b><br>600V, 13A<br>-40°C to +105°C<br>10mm OD                              | Industry Standard PVC                                      | <b>North American</b><br>1. Green/Yellow<br>2. Black<br>3. White                             | <br>7/8"-16UN2  |
|                                                                                     | MINM-3FP-*-R                                          | Yellow PVC<br>STOOW<br>With Foil Shield<br><b>3 X 16 AWG</b><br>600V, 13A<br>-40°C to +105°C<br>10mm OD   | Industry Standard PVC<br>Foil Shield                       |                                                                                              |                                                                                                     |
|                                                                                     | MINP-3FP-*-R                                          | Yellow PUR<br>AWM<br><b>3 X 16 AWG</b><br>600V, 13A<br>-40°C to +80°C<br>10mm OD                          | Oil and Cutting Fluid<br>Resistant<br>Cut Resistant<br>PUR |                                                                                              |                                                                                                     |
|                                                                                     | MINW-3FP-*-R<br>(YELLOW)<br>MINW-3FP-*-B-R<br>(BLACK) | TPE<br>SEOOW<br><b>3 X 16 AWG</b><br>600V, 13A<br>-40°C to +80°C<br>10mm OD                               | Weld Slag<br>Resistant TPE                                 |                                                                                              |                                                                                                     |
|                                                                                     | MIN-3FP-*-A-R                                         | Yellow PVC<br>STOOW<br><b>3 X 16 AWG</b><br>600V, 13A<br>-40°C to +105°C<br>10mm OD                       | Industry Standard PVC                                      | <b>North American<br/>Auto Color Code</b><br>1. Green/Yellow<br>2. Red/Black<br>3. Red/White |                                                                                                     |
|  | MIN-4FP-*-R<br>(YELLOW)<br>MIN-4FP-*-R-B<br>(BLACK)   | PVC<br>STOOW<br><b>4 X 16 AWG</b><br>600V, 10A<br>-40°C to +105°C<br>10.8mm OD                            | Industry Standard PVC                                      | <b>North American</b><br>1. Black<br>2. White<br>3. Red<br>4. Green/Yellow                   | <br>7/8"-16UN2 |
|                                                                                     | MINM-4FP-*-R                                          | Yellow PVC<br>STOOW<br>With Foil Shield<br><b>4 X 16 AWG</b><br>600V, 10A<br>-40°C to +105°C<br>10.8mm OD | Industry Standard PVC<br>Foil Shield                       |                                                                                              |                                                                                                     |

\* Lengths in feet. Standard cable lengths are 3, 6, 12, 20, 30 & 50 feet. Consult factory for other lengths.

Standard coupling nut is nickel plated brass, for stainless steel coupling nut add a "-SS" suffix. (e.g. MIN-4FP-3-R becomes MIN-4FP-3-R-SS)

See Page A-33 for Armored Cordset options.