



MIL-SPEC Series Cordsets


2 & 3 Conductor 5015 Industrial Equiv. Cordsets, 16AWG



Straight Male Cordsets | Size 10SL | 600 Volt, 13 amps | IP67 Rating



F
MIL-SPEC

Connector Body Style	Part Number	Cables	Features	Color Code	Faceview
	MS10SL-2MP-**	Yellow PVC STOOW 2 X 16 AWG 600V, 13A -40°C to +150°C 9.5mm OD	Industry Standard PVC	North American A. White B. Black	 10SL-2 0.6250"-24NEF
	MS10SL-3MP-** (Yellow) MS10SL-3MP-**-B (Black)	PVC STOOW 3 X 16 AWG 600V, 13 A -40°C to 105°C 10mm OD	Industry Standard PVC	North American A. Green/Yellow B. Black C. White	 10SL-3 0.6250"-24NEF
	MS10SLP-3MP-**	Yellow PUR AWM 3 X 16 AWG 600V, 13A -40°C to 80°C 10mm OD	Oil and Cutting Fluid Resistant Cut Resistant PUR		
	MS10SLW-3MP-** (YELLOW) MS10SLW-3MP-**-B (BLACK)	TPE SEOOW 3 X 16 AWG 600V, 13A -40°C to 80°C 10mm OD	Weld Slag Resistant TPE		

** Lengths in meters. Standard Cable lengths are 1, 2, 4, 5, 6, 10 & 15 meters. Consult factory for other lengths.

Standard coupling nut is nickel plated aluminum, for black anodized aluminum coupling nut add a "-BA" suffix. (e.g. MS10SL-3MP-1M becomes MS10SL-3MP-1M-BA)