



REVISIONS		
REV.	DESCRIPTION	DATE
A	REDRAWN IN SW	2/25/2005
B	ADDED TABLE WITH R AND B	6/1/2006

MATERIALS	
BODY:	GRAY POLYAMIDE
GROMMET:	NEOPRENE

SPECIFICATIONS:	
TIGHTENING TORQUE:	5.0 Nm
TEMPERATURE:	-20°C - +100°C

APPROVALS:	
US	UL RECOGNIZED
CANADA	C-UL RECOGNIZED

NO O-RING IS NECESSARY TO OBTAIN IP68 SEAL. CRUSH RIBS ON THE UNDERSIDE OF HEX WILL PROVIDE THE SEAL.

SEAL RATED TO: IP68

PART NUMBER	COLOR	SEALING RANGE
PCG-1/2	GRAY	.394 - .551 [10 - 14 MM]
PCG-1/2R	GRAY	.276 - .472 [7 - 12mm]
PCG-1/2-B	BLACK	.394 - .551 [10 - 14 MM]
PCG-1/2R-B	BLACK	.276 - .472 [7 - 12mm]

UNLESS OTHERWISE SPECIFIED:		NAME	MENCOM CORPORATION	
DIMENSIONS ARE IN INCHES		BEM		
MATERIAL		DRAWN	TITLE:	
		CHECKED		
		ENG APPR.		
		MFG APPR.		
		Q.A.		
FINISH		COMMENTS:	SIZE DWG. NO.	
DO NOT SCALE DRAWING			REV	
SPECIFICATIONS			SCALE: 3:1 WEIGHT:	
			SHEET 1 OF 1	

**PROPRIETARY AND CONFIDENTIAL**  
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS PROHIBITED.