



MATERIALS	
BODY:	GRAY POLYAMIDE
GROMMET:	NEOPRENE
SPECIFICATIONS:	
TIGHTENING TORQUE:	7.5 Nm
TEMPERATURE:	-20°C - +100°C

APPROVALS:	
US	UL RECOGNIZED
CANADA	C-UL RECOGNIZED

PROPRIETARY AND CONFIDENTIAL  
THE INFORMATION CONTAINED IN THIS  
DRAWING IS THE SOLE PROPERTY OF  
MENCOM CORPORATION. ANY  
REPRODUCTION IN PART OR AS A WHOLE  
WITHOUT THE WRITTEN PERMISSION OF  
MENCOM CORPORATION IS  
PROHIBITED.

NO O-RING IS NECESSARY TO OBTAIN IP68 SEAL. CRUSH RIBS  
ON THE UNDERSIDE OF HEX WILL PROVIDE THE SEAL.

SEALING RANGE: .512 - .708 (13 - 18 MM)  
SEAL RATED TO: IP68

UNLESS OTHERWISE SPECIFIED:  DIMENSIONS ARE IN INCHES AND [MM]	DRAWN BY	JJH	MENCOM CORPORATION		
	DRAWN DATE	09/07/2018			
	CHECKED BY	DCG	TITLE:  PG21 CABLE GLAND WITH FLEX TOP		
	CHECK DATE	09/07/2018			
MATERIAL  FINISH  DO NOT SCALE DRAWING	COMMENTS:		SIZE	DWG. NO.	REV
			B	PCG-21S	A
			SCALE: 2:1	WEIGHT:	SHEET 1 OF 1