

# Push-in T-connector CRQST-16

Part number: 130673

FESTO



## Data sheet

| Feature                                         | Value                                                                                                                                        |
|-------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------|
| Size                                            | Standard                                                                                                                                     |
| Maritime classification                         | See certificate                                                                                                                              |
| Design                                          | T-shape                                                                                                                                      |
| Nominal width                                   | 9.7 mm                                                                                                                                       |
| Type code                                       | CRQST                                                                                                                                        |
| Mounting position                               | Any                                                                                                                                          |
| Pack size                                       | 1                                                                                                                                            |
| Design                                          | Push-pull principle                                                                                                                          |
| Operating pressure for entire temperature range | -0.95 bar ... 10 bar                                                                                                                         |
| Operating medium                                | Compressed air as per ISO 8573-1:2010 [7:-:-]<br>Water as per manufacturer's declaration at <a href="http://www.festo.com">www.festo.com</a> |
| Information on operating and pilot media        | Operation with oil lubrication possible                                                                                                      |
| Corrosion resistance class (CRC)                | 4 - Particularly high corrosion stress                                                                                                       |
| For use in the food industry                    | See supplementary material information                                                                                                       |
| Ambient temperature                             | -15 °C ... 120 °C                                                                                                                            |
| Product weight                                  | 126 g                                                                                                                                        |
| No. of outlets                                  | 2                                                                                                                                            |
| No. of supply lines                             | 1                                                                                                                                            |
| Usable connector cables                         | PFAN                                                                                                                                         |
| Pneumatic connection 1                          | for pneumatic tubing outside diameter 16 mm                                                                                                  |
| Pneumatic connection 2                          | for pneumatic tubing outside diameter 16 mm                                                                                                  |
| Note on materials                               | RoHS-compliant                                                                                                                               |
| Housing material                                | High-alloy stainless steel                                                                                                                   |
| Releasing ring material                         | High-alloy stainless steel                                                                                                                   |
| Material of tubing seal                         | FPM                                                                                                                                          |
| Material of tube retaining claw                 | High-alloy stainless steel                                                                                                                   |