

# Push-in T-fitting QSYLV-1/8-3/16-U

Part number: 153794

**FESTO**



## Data sheet

| Feature                                         | Value                                         |
|-------------------------------------------------|-----------------------------------------------|
| Size                                            | Standard                                      |
| Maritime classification                         | See certificate                               |
| Type code                                       | QSYLV                                         |
| Type of seal on screwed trunion                 | Coating                                       |
| Mounting position                               | Any                                           |
| Pack size                                       | 1                                             |
| Design                                          | Push-pull principle                           |
| Operating pressure for entire temperature range | -0.95 bar ... 10 bar                          |
| Operating medium                                | Compressed air as per ISO 8573-1:2010 [7:-:-] |
| Information on operating and pilot media        | Operation with oil lubrication possible       |
| Corrosion resistance class (CRC)                | 1 - Low corrosion stress                      |
| Ambient temperature                             | -10 °C ... 60 °C                              |
| Max. tightening torque                          | 8 Nm                                          |
| No. of outlets                                  | 2                                             |
| No. of supply lines                             | 1                                             |
| Pneumatic connection 1                          | external thread 1/8 NPT                       |
| Pneumatic connection 2                          | for pneumatic tubing outside diameter 3/16"   |
| Releasing ring color                            | Gray                                          |
| Note on materials                               | RoHS-compliant                                |
| Housing material                                | PBT                                           |
| Releasing ring material                         | POM                                           |
| Material of tubing seal                         | NBR                                           |
| Material of tube retaining claw                 | High-alloy stainless steel                    |