

# Push-in L-fitting CRQSL-M5-4

Part number: 162870

**FESTO**



## Data sheet

| Feature                                         | Value                                                                                                                                        |
|-------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------|
| Size                                            | Standard                                                                                                                                     |
| Maritime classification                         | See certificate                                                                                                                              |
| Type of mounting                                | External hexagon, AF 10                                                                                                                      |
| Design                                          | L-shape                                                                                                                                      |
| Nominal width                                   | 2 mm                                                                                                                                         |
| Type code                                       | CRQSL                                                                                                                                        |
| Type of seal on screwed trunnion                | Sealing ring                                                                                                                                 |
| Mounting position                               | Any                                                                                                                                          |
| Pack size                                       | 1                                                                                                                                            |
| Design                                          | Push-pull principle                                                                                                                          |
| Operating pressure for entire temperature range | -0.95 bar ... 10 bar                                                                                                                         |
| Operating medium                                | Compressed air as per ISO 8573-1:2010 [7:-:-]<br>Water as per manufacturer's declaration at <a href="http://www.festo.com">www.festo.com</a> |
| Information on operating and pilot media        | Operation with oil lubrication possible                                                                                                      |
| Corrosion resistance class (CRC)                | 4 - Particularly high corrosion stress                                                                                                       |
| For use in the food industry                    | See supplementary material information                                                                                                       |
| Ambient temperature                             | -15 °C ... 120 °C                                                                                                                            |
| Nominal tightening torque                       | 1.33 Nm                                                                                                                                      |
| Tolerance for nominal tightening torque         | ± 20%                                                                                                                                        |
| Product weight                                  | 12 g                                                                                                                                         |
| Usable connector cables                         | PFAN                                                                                                                                         |
| Pneumatic connection 1                          | External thread M5                                                                                                                           |
| Pneumatic connection 2                          | for pneumatic tubing outside diameter 4 mm                                                                                                   |
| Note on materials                               | RoHS-compliant                                                                                                                               |
| Housing material                                | High-alloy stainless steel                                                                                                                   |
| Releasing ring material                         | High-alloy stainless steel                                                                                                                   |
| Material of tubing seal                         | FPM                                                                                                                                          |
| Material of tube retaining claw                 | High-alloy stainless steel                                                                                                                   |