



Air solenoid valve NVF3-MOH-5/2-K-1/4-EX

Part number: 535987

FESTO



Data sheet

Feature	Value
Valve function	5/2 or 3/2, monostable
Lap	Underlap
Actuation type	Electrical
Width	53 mm
Standard nominal flow rate	900 l/min
Pneumatic working port	Sub-base
Operating voltage	Via solenoid coil, to be ordered separately
Operating pressure	2 bar ... 10 bar
Design	Plate seat
Reset method	Mechanical spring
Nominal width	7 mm
Type code	NVF3
Exhaust air function	With flow control option
Sealing principle	Soft
Mounting position	Any
Conforms to standard	VDI/VDE 3845 (NAMUR)
Manual override	Detenting Non-detenting
Type of control	Pilot-controlled
Flow direction	Non-reversible
Symbol	00991831
b-value	0.33
C value	4.2 l/sbar
Switching time off	100 ms
On switching time	50 ms
ATEX category gas	II 2G
Type of ignition protection for gas	Ex h IIC T6 Gb
ATEX category for dust	II 2D
Type of (ignition) protection for dust	Ex h IIIC T70°C Db
Explosive ambient temperature	-5°C ≤ Ta ≤ +40°C
Explosion prevention and protection	Zone 1 (ATEX) Zone 2 (ATEX) Zone 21 (ATEX) Zone 22 (ATEX)
Operating medium	Compressed air as per ISO 8573-1:2010 [7:4:4]
Information on operating and pilot media	Operation with oil lubrication possible (required for further use)
CE marking (see declaration of conformity)	as per EU explosion protection directive (ATEX)

Feature	Value
Corrosion resistance class (CRC)	1 - Low corrosion stress
Temperature of medium	-5 °C ... 40 °C
Ambient temperature	-5 °C ... 40 °C
Product weight	280 g
Type of mounting	On terminal strip
Venting hole connection	Internal
Pilot exhaust air port 84	M5
Pneumatic connection 1	G1/4
Pneumatic connection 2	NAMUR connection diagram
Pneumatic connection 3	G1/4
Pneumatic connection 4	NAMUR connection diagram
Pneumatic connection 5	G1/4
Seals material	NBR
Housing material	Die-cast aluminum