

WIRING	
1 --- 1	
2 --- 2	
3 --- 3	

KEYWAY LOCATOR SYMBOL

CAUTION LABEL

PRODUCT LABEL

[39] 1.5

1-3/8-16UN2A

[101] 4.0

L

[108] 4.3

1-3/8-16UN2B FEMALE THREAD

[39] 1.5

P/N	L	STD?
PMIN-30MFP-1M	40" [1m]	YES
PMIN-30MFP-2M	79" [2m]	YES
PMIN-30MFP-3M	117" [3m]	NO
PMIN-30MFP-4M	157" [4m]	YES
PMIN-30MFP-5M	197" [5m]	YES
PMIN-30MFP-6M	236" [6m]	NO
PMIN-30MFP-8M	315" [8m]	NO
PMIN-30MFP-10M	393" [10m]	YES
PMIN-30MFP-15M	590" [15m]	YES
PMIN-30MFP-20M	787" [20m]	YES

PARTS LISTED AS NOT BEING STANDARD
MAY REQUIRE MINIMUM ORDERS
OTHER LENGTHS AVAILABLE,
PLEASE CONSULT FACTORY

MENCOM CORPORATION
TITLE:
3 PL M-F EXT PLG PMIN
10AWG

SIZE B DWG. NO. PMIN-30MFP-ZZ REV B

SCALE: 1:1 WEIGHT: SHEET 1 OF 1

MATERIALS	
BODY:	BLACK PVC
INSERT:	BLACK PVC
CONTACTS:	GOLD PLATED COPPER ALLOY
CABLE:	10/3 STOOW GRAY PVC
COUPLING:	NICKEL PLATED BRASS

RATINGS:	
SCCR RATING:	65kA Breakers and Fuses
RoHS COMPLIANT:	Yes
PROTECTION:	IP67
UL CATEGORY:	PVVA (US), PVVA7 (Canada)
U.S.	UL 2237 LISTED, File E469485
CANADA	C-UL 2237 LISTED, File E469485

CAUTION:
RISK OF ELECTRICAL SHOCK
DO NOT DISCONNECT UNDER LOAD

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS PROHIBITED.

VOLTS 600V
AMPS 35A
TEMP: -40° TO 90°C

UNLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN INCHES AND [MM]

MATERIAL FINISH DO NOT SCALE DRAWING

DRAWN BY ADM
DRAWN DATE 06/22/2020
CHECKED BY GO
CHECK DATE 06/23/2020
COMMENTS: