	8 7	6	5	4	3	2	1	
PIN #	COLOR							
1	BLACK							
2	GREEN/YELLOW							
3	WHITE			PRODUCT LABEL				
	1.375-16L	N2B						
_			[51] 2.0					
[3	38] 1.5					P/N	L	
	20					PMIN-34FR-0.3	M-34 12" [0.3m]	
					i \	PMIN-34FR-0.51	A-34 20" [0.5m]	
Þ						PMIN-34FR-1M		
				3/4-	14 NPT	PMIN-34FR-2M		
						PMIN-34FR-3M		
MATERIAL	IS			◄	I^			
						PMIN-34FR-4M		
BODY:	NICKEL PLATED BRASS					PMIN-34FR-5M		
CONTACT		LOY				PMIN-34FR-6M-	34 236" [6m]	
INSERT: WIRE:			CAL	ITION:		PMIN-34FR-8M	34 315" [8m]	
	14AWG UL1015 ZINC PLATED STEEL					PMIN-34FR-10N	1-34 393" [10m]	
GASKET:	TPE			NECT UNDER LOAD		OTHER LENGTH CONSULT F		
RATINGS): 				UNLESS OTHERWISE SPECIFIED: DRAWN BY		ORPORATION	
SCCR RA	TING: 65kA Breakers and	Fuses			DIMENSIONS ARE IN INCHES DRAWN D. AND [MM] CHECKED			
RoHS CO	OMPLIANT: Yes			CHECK DATE 06/23/2020 3 PL FEM			MIN RCP 3/4	
PROTECT	TION: IP67		PROPRIETARY AND CONFIDENT	al VOLTS 600V		N	IPT	
UL CATE	GORY: PVVA (US), PVVA7 (Canada)	THE INFORMATION CONTAINED IN DRAWING IS THE SOLE PROPERTY C		MATERIAL	SIZE DWG. NO.	REV	
U.S.	UL 2237 LISTED, Fi	e E469485	MENCOM CORPORATION, ANY REPRODUCTION IN PART OR AS A V WITHOUT THE WRITTEN PERMISSION		PC FINISH	B PMIN-34	FR-ZZ-34 B	
CANADA	C-UL 2237 LISTED,	File E469485	MENCOM CORPORATION IS PROHIBITED.		DO NOT SCALE DRAWING	SCALE: 3:2 WEIGHT:	Sheet 1 of 1	