8		7	6	5	4	3		2	1
PIN #COLOR1BLACK2GREEN/YE3RED4WHITE	LLOW			[48] 1.9	[13] .5		PRC	DUCT LABEL	
[38] 1.5 (P/N	L
V						/4-14 NPT			10" [0 2m]
								PMIN-42MR-0.3M-34	
		1.375-16UN2A-						PMIN-42MR-0.5M-34	
					-	— L ———//		PMIN-42MR-1M-34	40" [1m]
			1				ľ	PMIN-42MR-2M-34	79" [2m]
MATERIALS			_					PMIN-42MR-3M-34	117" [3m]
			-					PMIN-42MR-4M-34	157" [4m]
BODY: NICKEL PLATED BRASS CONTACTS: GOLD PLATED COPPER ALLOY			-					PMIN-42MR-5M-34	197" [5m]
	CK PVC	PERALLOY	_					PMIN-42MR-6M-34	
	WG UL1015		-						236" [6m]
JAM NUT: ZINC PLATED STEEL			-	CAUT	ION:			PMIN-42MR-8M-34	315" [8m]
GASKET: TPE				RISK OF ELECT	RICAL SHOCK			PMIN-42MR-10M-34	393" [10m
RATINGS:				DO NOT DISCONNE	CT UNDER LOAD			OTHER LENGTHS CONSULT FA	
						UNLESS OTHERWISE SPECIFIED: DRAWN	BY		
SCCR RATING:	65kA Breaker	s and Fuses				AND [MM]	DATE 06/22/2020	MENCOM CORPO	
RoHS COMPLIANT:	Yes					CHECK E		-	
PROTECTION:	IP67							4 PL MAL PMIN F NPT 12AW	-
UL CATEGORY:	PVVA (US), PV	/VA7 (Canada)		PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS	VOLTS 600V	COMM	MENTS:	SIZE DWG. NO.	REV
U.S.		ED, File E469485		DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE	AMPS 25A TEMP: -40°C TO 90°	FINISH		B PMIN-42MR-ZZ	
CANADA		TED, File E469485		WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS PROHIBITED.	TEMP: -40°C TO 90°	C DO NOT SCALE DRAWING		SCALE: 3:2 WEIGHT:	SHEET 1 OF 1
8		7	6	5	4	BO NOT SCALE DRAWING		2	1