



PIN #	COLOR
1	BLACK
2	GREEN / YELLOW
3	WHITE



P/N	L	STD?
PMINW-34FP-1M-C011	40" [1m]	YES
PMINW-34FP-2M-C011	79" [2m]	YES
PMINW-34FP-3M-C011	117" [3m]	YES
PMINW-34FP-4M-C011	157" [4m]	YES
PMINW-34FP-5M-C011	197" [5m]	YES
PMINW-34FP-6M-C011	236" [6m]	NO
PMINW-34FP-8M-C011	315" [8m]	NO
PMINW-34FP-10M-C011	393" [10m]	YES
PMINW-34FP-15M-C011	590" [15M]	YES
PMINW-34FP-20M-C011	787" [20M]	YES

MATERIALS	
BODY:	BLACK PVC
INSERT:	BLACK PVC
CONTACTS:	GOLD PLATED COPPER ALLOY
CABLE:	14/3 TC-ER FT4 BLK TPE JKT
COUPLING:	NICKEL PLATED BRASS

RATINGS:	
SCCR RATING:	65kA Breakers and Fuses
RoHS COMPLIANT:	Yes
PROTECTION:	IP67
UL CATEGORY:	PVVA (US), PVVA7 (Canada)
U.S.	UL 2237 LISTED, File E469485
CANADA	C-UL 2237 LISTED, File E469485

**CAUTION:**  
**RISK OF ELECTRICAL SHOCK**  
**DO NOT DISCONNECT UNDER LOAD**

PROPRIETARY AND CONFIDENTIAL  
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS PROHIBITED.

**VOLTS** 600V  
**AMPS** 24A  
**TEMP:** -40° to 90°C

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES AND [MM]	DRAWN BY	ADM
	DRAWN DATE	06/23/2020
	CHECKED BY	GO
	CHECK DATE	06/23/2020
COMMENTS:		
MATERIAL		
FINISH		
DO NOT SCALE DRAWING		

PARTS LISTED AS NOT BEING STANDARD  
MAY REQUIRE MINIMUM ORDERS

<b>MENCOM CORPORATION</b>		
TITLE: <b>3 PL FEM PLG PMIN 14AWG</b>		
SIZE	DWG. NO.	REV
<b>B</b>	PMINW-34FP-ZZ-C011	<b>B</b>
SCALE: 1:1	WEIGHT:	SHEET 1 OF 1