



YAS30R2NTN

by Burndy
Catalog ID: YAS30R2NTN

Prop 65 Notice

Aluminum Stacking terminal - Straight lug, 250, 300 Kcmil Al, 266 Kcmil Cu ACSR, Blue, Tin plated

Product Details

General

Color Code	Blue
Connector Type	Terminal
Die Index	317;705;CSA26;K-1-1/8-1
Feature - Barrel Style	Chamfered
Material	Aluminum
Physical Attribute - Number of Holes	2
Plated	Y
Plating Type	Tin - Electro Plated
Trade Name	HYLUG™
UPC	781810416648
UPC 12 Digit	7818104166488

Dimensions

Dimension - B Length inch	1.85 in
Dimension - D inch	4.17 in
Dimension - Hole Size inch	0.56 in
Dimension - Inside Diameter inch	0.67 in
Dimension - L Length Overall mm	167 mm
Dimension - Length Overall inch	6.59 in
Dimension - N inch	0.63 in
Dimension - Outside Diameter inch	1.24 in
Dimension - P inch	2.43 in
Dimension - Pad Width inch	1.22 in
Dimension - Strip Length inch	2 in
Dimension - Z inch	1.79 in
Physical Attribute - Tongue Angle	Straight

Conductor Related

Conductor - ACSR Str Size	266.8 (18/1) Waxwing kcmil
Conductor - ACSR Str Size Range	266.8 (18/1) Waxwing kcmil
Conductor - AL Str Size	250 kcmil;266 kcmil;300 kcmil

Conductor - AL Str Size Range	250 kcmil-300 kcmil
Conductor - Copper Str Size	250 kcmil;300 kcmil
Conductor - Copper Str Size Range	250 kcmil-300 kcmil

Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	CM
UL Listed	No

Logistics

Minimum Pack Quantity	1
-----------------------	---

For further technical assistance, please contact us

BURNDY Headquarters
47 East Industrial Park Drive
Manchester, New Hampshire 03109

Customer Service Hours:
8 AM - 8 PM Eastern Monday-Friday
Emergency Service 24-hours/365 Days
Phone: 1-800-346-4175
1-603-647-5299 (International)