



YC33R26

by Burndy
Catalog ID: YC33R26

Prop 65 Notice

Al Compression Tap(C-Shaped),300-397.5 Kcmil Al, 336.4 Kcmil
ACSR(Run), 2 -2/0 Str. Al, 2 -1/0 AWG ACSR(Tap), 1.56"

Product Details

General

Die Index	R
Material	Aluminum
Plated	N
Plating Type	Unplated
Trade Name	CRIMPIT™
Type	YC-A, YC-U Series
UPC	781810127001
UPC 12 Digit	7818101270011

Dimensions

Dimension - Height inch	1.98 in
Dimension - L Length Overall mm	40 mm
Dimension - Length Overall inch	1.56 in

Conductor Related

Conductor - AAAC 5005 Run	394.5 (19) kcmil
Conductor - AAAC 5005 Run Range	394.5 (19) kcmil
Conductor - AAAC 5005 Tap	77.47 (7) kcmil;123.3 (7) kcmil
Conductor - AAAC 5005 Tap Range	77.47 (7) kcmil-123.3 (7) kcmil
Conductor - AAAC 6201 Run	394.5 (19) kcmil
Conductor - AAAC 6201 Run Range	394.5 (19) kcmil
Conductor - AAAC 6201 Tap	77.47 (7) kcmil;123.3 (7) kcmil
Conductor - AAAC 6201 Tap Range	77.47 (7) kcmil-123.3 (7) kcmil
Conductor - ACSR Cmpt Run	336.4 kcmil
Conductor - ACSR Cmpt Run Range	336.4 kcmil
Conductor - ACSR Cmpt Tap	2 AWG;1 AWG;1/0 AWG
Conductor - ACSR Cmpt Tap Range	2 AWG-1/0 AWG
Conductor - ACSR Str Run	336.4 Kcmil
Conductor - ACSR Str Tap Range	2 AWG - 1/0 AWG
Conductor - AL Str Run	336.4 Kcmil
Conductor - AL Str Run Range	300 kcmil-397 kcmil

Conductor - AL Str Tap	2 AWG;1 AWG;1/0 AWG;2/0 AWG
Conductor - AL Str Tap Range	2 AWG - 2/0 AWG

Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	CM
UL Listed	No

Logistics

Minimum Pack Quantity	1
-----------------------	---

For further technical assistance, please contact us

BURNDY Headquarters
47 East Industrial Park Drive
Manchester, New Hampshire 03109

Customer Service Hours:
8 AM - 8 PM Eastern Monday-Friday
Emergency Service 24-hours/365 Days
Phone: 1-800-346-4175
1-603-647-5299 (International)