



* Representative image

#6 - #2 Compression Splice VERSA-CRIMP®

by ANDERSON
Catalog ID: VCJS36R

Partial Tension VersaCrimp Aluminum Compression Splice for #6 (7), #4 (7), #3 (7), #2 (7) (19) AAC, #6 (6/1), #4 (7/1) (6/1), #2 (7/1), (6/1) ACSR

- For use with VC6 (all) tools only
- Partial tension (40% tension rating) jumping splice
- Can be used with compressed (compact) conductor sizes within the same decimal range

Product Details

General

Compression Method	VersaCrimp Tooling ONLY VC6 (all)
Compression Tool Type	VersaCrimp Tooling ONLY VC6 (all)
Material	Aluminum
UPC	096359336747

Dimensions

Length Before Compression	4.62 in
Weight	0.098 lb

Conductor Related

Conductor Compatibility	ACSR-Turkey-6-6/1;ACSR-Swan-4-6/1;ACSR-Swanate-4-7/1;ACSR-Sparrow-2-6/1;ACSR-Sparate-2-7/1;AAC-Peachbell-6-7;AAC-Rose-4-7;AAC-Iris-2-7;AAAC 6201 Alloy-Akron-30.58-6/18;AAAC 6201 Alloy-Alton-48.69-6/18;AAAC 6201 Alloy-Ames-77.47-6/18
Conductor Diameter (VersaCrimp) - Maximum	0.325 in
Conductor Diameter (VersaCrimp) - Minimum	0.184 in

Certifications and Compliance

UL Listed	No
-----------	----

Logistics

Carton Quantity	149 EA
-----------------	--------

For further technical assistance, please contact us

Domestic Customer Service

Hubbell Power Systems
210 N. Allen Centralia, MO 65240 USA
Phone: (573) 682-5521
Fax: (573) 682-8475
Email: hpscscs@hubbell.com

International Customer Service

Phone: +1-573-682-5521
Fax: +1-573-682-8516
Email: hpsintlcs@hubbell.com