



* Representative image

250 - 556 MCM Compression Splice VERSA-CRIMP®

by ANDERSON
Catalog ID: VCJS831R

Partial Tension VersaCrimp Aluminum Compression Splice for 250 (19, 37), 266 (7, 19), 300 (37), 336 (19), 350 (19, 37), 397 (19), 400 (37), 450 (19, 37), 477 (19, 37) AAC,

- For use with VC8 tools only
- Partial tension (40% tension rating) jumping splice
- Can be used with compressed (compact) conductor sizes within the same decimal range

Product Details

General

Compression Method	VersaCrimp Tooling ONLY VC8
Compression Tool Type	VersaCrimp Tooling ONLY VC8
Material	Aluminum
UPC	096359336761

Dimensions

Length Before Compression	11.12 in
Weight	1.274 lb

Conductor Related

Conductor Compatibility	ACSR-Waxwing-266.8-18/1;ACSR-Partridge-266.8-26/7;ACSR-Ostrich-300-26/7;ACSR-Merlin-336.4-18/1;ACSR-Linnet-336.4-26/7;ACSR-Oriole-336.4-30/7;ACSR-Chickadee-397.5-18/1;ACSR-Brant-397.5-24/7;ACSR-Ibis-397.5-26/7;ACSR-Lark-397.5-30/7;ACSR-Pelican-477-18/1;ACSR-Flicker-477-24/7;ACSR-Hawk-477-26/7;ACSR-Hen-477-30/7;ACSR-Osprey-556.5-18/1;ACSR-Brahma-203.2-16/19;AAC-Valerian-250-19;AAC-Laurel-266.8-19;AAC-Tulip-336.1-19;AAC-Daffodil-350-19;AAC-Canna-397.5-19;AAC-Cosmos-477-19;AAC-Syringa-477-37;AAC-Zinnia-500-19;AAC-Hyacinth-500-37;AAC-Dahlia-556.5-19;AAC-Mistletoe-556.5-37
Conductor Diameter (VersaCrimp) - Maximum	0.883 in
Conductor Diameter (VersaCrimp) - Minimum	0.574 in

Certifications and Compliance

UL Listed	No
-----------	----

For further technical assistance, please contact us

Domestic Customer Service

Hubbell Power Systems
210 N. Allen Centralia, MO 65240 USA
Phone: (573) 682-5521
Fax: (573) 682-8475
Email: hpscs@hubbell.com

International Customer Service

Phone: +1-573-682-5521
Fax: +1-573-682-8516
Email: hpsintlcs@hubbell.com