

# T-TYPE insulating STANDARD APPLICATIONS

inserts		page:
CDD	42 poles + ⊕	78
CDS	18 poles + ⊕	-
CDSH	18 poles + ⊕	87
CNE	10 poles + ⊕	111
CSE	10 poles + ⊕	-
CSH	10 poles + ⊕	111
CSH S	10 poles + ⊕	123
CCE	10 poles + ⊕	131
CMSH	3+2 (aux) poles + ⊕	136
CMCE	3+2 (aux) poles + ⊕	137
CSS	10 poles + ⊕	149
CT, CTSE (16A) *)	10 poles + ⊕	161
CQE	18 poles + ⊕	169
CX	8/24 poles + ⊕	194
MIXO	3 modules	262 - 317

\*) only for standard insulating version TCHI

## hoods with double lever top entry




## covers




description	part No.	entry M	part No. (with eyelet)	part No. (with loop)
with thermoplastic levers and gasket, high construction	<b>TMAV 10 G25</b>	25		
with thermoplastic levers and gasket, high construction	<b>TMAV 10 G32</b>	32		
with 4 pegs			<b>TCHC 10</b>	<b>TCHC 10 S</b>
with 2 thermoplastic levers and gasket				<b>TCHC 10 G</b>


### TMAV G



### TCHC (S)



### TCHC G




For fixing on housings

eyelet



For fixing on hoods

loop



**CAIUS**® Type 12



ambient temperature limits -40 °C / +90 °C