

YCA26R2N

by Burndy
Catalog ID: YCA26R2N

Prop 65 Notice

AL compression lug designed for terminating jumper loop and equipment taps to switch pads and other substation switch yard apparatus, 6.30 IN L.

Features: Compression Terminal, Tools, Die Set Catalog Number, And (number Of Crimps): MD6, MD7 Tool, W245 Die, (4), Y35, Y750 Tool, U245 Die, (2), Y45 Tool, U245 Die With PT-6515 Adapter, (2), Y46 Tool, U245 Die With PUADP-1 Adapter, (2), Y48B Tool, C245 Die, (2), Y60BHU Tool, L245 Die, (1), Conductor Type: ACSR/6201/5005 (Compressed/Compact), Aluminum, Die Index: 245 Or 9A

Product Details

General

Application	For ACSR/6201/5005 (Compressed/Compact), Aluminum
Connector Type	Terminal
Die Index	245;9A
Material	Aluminum
Physical Attribute - Pad Configuration	2 Hole NEMA
Plated	N
Plating Type	Unplated
Prefilled Oxide Inhibitor	Y
Sub Brand	TERMINAL,TERMINALS
Type	YCA-R-N, Terminal
UPC	781810810439
UPC 12 Digit	7818108104399

Dimensions

Dimension - B Length inch	2.43 in
Dimension - Bolt Hole Size inch	0.5 in
Dimension - E Spacing between Holes fraction	1-3/4 in
Dimension - L Length Overall mm	160 mm
Dimension - Length Overall inch	6.30 in
Dimension - Outside Diameter inch	0.70 in
Dimension - Pad Width inch	0.97 in

Conductor Related

Conductor - ACSR Str Size	2/0 (6/1) Quail AWG
Conductor - ACSR Str Size Range	2/0 (6/1) Quail AWG
Conductor - AL Str Size	2/0 AWG
Conductor - AL Str Size Range	2/0 AWG

Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	CM
UL Listed	No

Logistics

Minimum Pack Quantity	1
-----------------------	---

For further technical assistance, please contact us

BURNDY Headquarters
47 East Industrial Park Drive
Manchester, New Hampshire 03109

Customer Service Hours:
8 AM - 8 PM Eastern Monday-Friday
Emergency Service 24-hours/365 Days
Phone: 1-800-346-4175
1-603-647-5299 (International)