



YKA2C2N

by Burndy
Catalog ID: YKA2C2N

Prop 65 Notice

HYLUG™, Copper Disconnectable Compression Terminal, With Fixed H/W,
2 Holes, #2 Str Cu, 1/2" Stud

Product Details

General

Connector Type	Terminal
Die Index	163
Material	Copper
Physical Attribute - Number of Crimps Required	2
Physical Attribute - Number of Holes	2
Plated	Y
Plating Type	Tin
Prefilled Oxide Inhibitor	N
Trade Name	HYLUG™
UPC	781810014721

Dimensions

Dimension - B Length fraction	1-4/57 in
Dimension - B Length inch	1.07 in
Dimension - E Spacing between Holes fraction	1-3/4 in
Dimension - L Length Overall mm	129 mm
Dimension - Length Overall inch	5.06 in
Dimension - N inch	0.62 in
Dimension - Outside Diameter inch	0.5 in
Dimension - Pad Width inch	0.88 in
Dimension - Strip Length inch	1- 3/16 in
Dimension - Stud Size inch	1/2 in
Physical Attribute - Tongue Angle	Straight

Conductor Related

Conductor - Copper Str Size	2 AWG
Conductor - Copper Str Size Range	2 AWG

Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No

Certification - cULus	No
Standards - RoHS Compliance Status	EX
UL Listed	No

Logistics

Minimum Pack Quantity	1
-----------------------	---

For further technical assistance, please contact us

BURNDY Headquarters
47 East Industrial Park Drive
Manchester, New Hampshire 03109

Customer Service Hours:
8 AM - 8 PM Eastern Monday-Friday
Emergency Service 24-hours/365 Days
Phone: 1-800-346-4175
1-603-647-5299 (International)