

Plug-in relay 2 W, Width 15 mm, 24 V DC for LZS sockets

Figure similar

product brand name	SIRIUS
product designation	Plug-in relay
product type designation	LZX
General technical data	
consumed active power	400 mW
percental drop-out voltage related to the input voltage	10 %
shock resistance acc. to IEC 60068-2-27	5g / 11 ms
vibration resistance acc. to IEC 60068-2-6	30 ... 150 Hz: 5g
operating frequency without load	72 000 1/h
operating frequency with load	360 1/h
switching behavior	monostable
design of the switching function	changeover switch
design of the switching function positively driven	No
mechanical service life (switching cycles) typical	30 000 000
electrical endurance (switching cycles) at AC-15 at 230 V typical	100 000
thermal current	8 A
reference code acc. to IEC 81346-2	K
Substance Prohibitance (Date)	01.05.2012 00:00:00
Control circuit/ Control	
control supply voltage at DC	24 V
• rated value	
operating range factor control supply voltage rated value at DC	
• initial value	0.9
• full-scale value	1.4
design of the relay operating mechanism	poled
product component plug-in socket	No
Auxiliary circuit	
type of switching contact	Changeover contact
material of switching contacts	AgNi 90/10
number of NC contacts for auxiliary contacts	0
number of NO contacts for auxiliary contacts	0
number of CO contacts for auxiliary contacts	2
operational current of auxiliary contacts at AC-15	3 A
• at 250 V	
operational current at DC-13 at 24 V rated value	2 A

operational current of auxiliary contacts at DC-13		2 A	
• at 24 V			
Main circuit			
type of voltage		DC	
Outputs			
ampacity of the output relay at AC-15 at 250 V at 50/60 Hz		3 A	
ampacity of the output relay at DC-13		2 A	
• at 24 V			
Connections/ Terminals			
product function removable terminal		No	
Installation/ mounting/ dimensions			
mounting position		any	
fastening method		base mounting	
height		29 mm	
width		12.7 mm	
depth		19.5 mm	
Ambient conditions			
ambient temperature			
• during operation			
• during storage			
• during transport			
Certificates/ approvals			
General Product Approval		Declaration of Conformity	other



[Miscellaneous](#)

[Confirmation](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=LZX:RT424024>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=LZX:RT424024>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)



<https://support.industry.siemens.com/cs/ww/en/ps/LZX:RT424024>


Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=LZX:RT424024&lang=en

Characteristic: Derating

<https://support.industry.siemens.com/cs/ww/en/ps/LZX:RT424024/manual>





last modified:

12/23/2020 