Product data sheet Characteristics

XVR08B04

Harmony XVR, Rotating beacon, Ø84, red, without buzzer, 24 V AC/DC

Product availability: Stock - Normally stocked in distribution facility



Price*: 180.00 USD



Main

Man		<u>ŭ</u>
Range of product	Harmony XVR	
Product or component type	Prewired rotating mirror beacon	
Sound signalling	Without	±
Device short name	XVR	:-
Mounting diameter	3.31 in (84 mm)	<u> </u>
IP degree of protection	IP65 IEC 60529 with accessory) IP23 IEC 60529	irabilitv
[Us] rated supply voltage	24 V AC/DC	
Light source	High luminosity LED, red	<u></u>

Complementary

7		
, .		
Main		
Range of product	Harmony XVR	
Product or component type	Prewired rotating mirror beacon	
Sound signalling	Without	
Device short name	XVR	
Mounting diameter	3.31 in (84 mm)	
IP degree of protection	IP65 IEC 60529 with accessory) IP23 IEC 60529	
[Us] rated supply voltage	24 V AC/DC	
Light source	High luminosity LED, red	
Complementary Material	ABS (acrylonitrile butadiene-styrene) body part PC globe	
CAD overall width	3.31 in (84 mm)	
CAD overall depth	3.31 in (84 mm)	
Net Weight	0.66 lb(US) (0.3 kg)	
Marking	CE	
Product mounting	By 3 M4 screws	
Supply voltage limits	1930 V DC 21.626.4 V AC	
[Uimp] rated impulse withstand voltage	0.8 kV	
Current consumption	125 mA	
Flashing frequency	2.3 Hz	
Clamping connection capacity	0.83 mm²	
AWG gauge	AWG 18	
Cable length	19.69 in (500 mm)	
Price is "List Price" and may be subject to a trade dis-	count – check with your local distributor or retailer for actual price.	
I.I.20, 2024		

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Environment

Standards	EN 61000-6-4
	EN 61000-6-2
Product certifications	UL
Protective treatment	TC
Ambient air temperature for storage	-31158 °F (-3570 °C)
Ambient air temperature for operation	14122 °F (-1050 °C)
Electrical shock protection class	Class II IEC 61140

Ordering and shipping details

Category	22617 - XVC TOWER LIGHTS
Discount Schedule	XV
GTIN	03606480032998
Nbr. of units in pkg.	1
Package weight(Lbs)	13.72 oz (389 g)
Returnability	Yes
Country of origin	ID

Packing Units

. c.cg cc	
Unit Type of Package 1	PCE
Package 1 Height	7.28 in (18.5 cm)
Package 1 width	3.86 in (9.8 cm)
Package 1 Length	3.86 in (9.8 cm)
Unit Type of Package 2	S03
Number of Units in Package 2	6
Package 2 Weight	6.90 lb(US) (3.132 kg)
Package 2 Height	11.81 in (30 cm)
Package 2 width	11.81 in (30 cm)
Package 2 Length	15.75 in (40 cm)

Offer Sustainability


Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	End of Life Information	


Contractual warranty

Warranty	18 months

Rotating Mirror Beacon

Dimensions





Product data sheet Mounting and Clearance

XVR08B04

Rotating Mirror Beacon

Panel Cut-out

