




Basic features

Approval/Conformity	CE
	cULus
	EAC
	WEEE
Scope of delivery	Part label (20x)
	Port cover M12 (4x)
	Grounding strap
	Lock washer
	Short guide
	M4x6 screw
Style	Two-row

Display/Operation

Actuator supply UA, indicator	Green LED
IO-Link communication indicator	Green LED
Module supply indicator	Green LED
Sensor supply US indicator	Green LED
Switching function display	LED yellow

Electrical connection

Connection (COM 1)	M12x1-Male, 4-pin, A-coded
Connection (supply voltage IN)	7/8"-Male, 5-pin
Connection slots	8x M12x1-Female, 5-pin, A-coded
Contact, surface protection	nickel plated 2 µm/gold plated 0.4 µm

Electrical data

Configurable inputs/outputs	yes
Current consumption without load, max.	50 mA
Current sum UA, actuator	9.0 A
Current sum US, sensor	9.0 A
IO-Link function	Device
IO-Link ports, number	1
Operating voltage Ub	18...30.2 VDC
Rated operating voltage Ue DC	24 V
Switching current	16x 2 A

Environmental conditions

Ambient temperature	-5...55 °C
EN 60068-2-6, Vibration	5...61 Hz, constant amplitude 1 mm 61...500 Hz, constant acceleration 15 g
IP rating	IP67, when threaded in
Storage temperature	-25...70 °C

Functional safety

MTTF (40 °C)	38.7 a
--------------	--------

Material

Gasket, material	FKM 75
Housing material	Zinc, Die casting
Housing shield	yes
Surface protection	Cu 15 µm Ni 15 µm

Mechanical data

Dimension	68 x 32.4 x 181.5 mm
Mounting ground strap	M4 internal thread
Mounting part	2-hole screw mount

Output/Interface

Cycle time min.	6.2 ms
Digital inputs	16x PNP, Type 3
Digital outputs	16x PNP
Extension port	yes
IO-Link version	1.1
Interface	IO-Link 1.1
Process data IN	8 bytes
Process data OUT	2 bytes
Process data cycle min.	6.2 ms
Single-channel monitoring	yes
Transfer rate	COM2 (38.4 kBaud)


Remarks

See short guide

For more information about MTTF and B10d see MTTF / B10d Certificate


Indication of the MTTF- / B10d value does not represent a binding composition and/or life expectancy assurance; these are simply experiential values with no warranty implications. These declared values also do not extend the expiration period for defect claims or affect it in any way.

Connector Drawings




I/O ports

PIN 1: +24V, 300mA
PIN 2: Input/Output 2
PIN 3: GND
PIN 4: Input/Output 1
PIN 5: Function ground



Power IN

PIN 1: GND, reference potential
PIN 2: GND, reference potential
PIN 3: Function ground
PIN 4: +24V, US
PIN 5: +24V, UA



IO-Link

PIN 1: +24V
PIN 2: n.c.
PIN 3: GND
PIN 4: C/Q, IO-Link DC-Channel