



MDC (M12) Series Cordsets

5 Conductor MDC Series Cordsets, 18/22AWG





Straight Male Cordsets | 300 Volt, 4 amps | IP69 Rating



H

Micro-DC (M12) Series Cordsets

Connector Body Style	Part Number	Cables	Features	Color Code	Faceview
	MDC-5MPX-** (Yellow) MDC-5MPX-**-B (Black)	Yellow PVC AWM 5 X 18 AWG 300V, 4A -40°C to +105°C 7.4mm OD	Industry Standard PVC	1. Brown 2. White 3. Blue 4. Black 5. Gray	 M12x1
	MDC-5MP-** (Yellow) MDC-5MP-**-B (Black)	PVC AWM 5 X 22 AWG 300V, 4A -40°C to +105°C 5.8mm OD	Industry Standard PVC		
	MDCM-5MP-**	Yellow PVC AWM With Foil Shield 5 X 22 AWG 300V, 4A -40°C to +105°C 5.8mm OD	Industry Standard PVC Foil Shield		
	MDCM-5MSP-**	Yellow PVC AWM With Foil Shield 5 X 22 AWG 300V, 4A -40°C to +105°C 5.8mm OD	Industry Standard PVC Foil Shield to the Coupling Nut		
	MDCP-5MP-**	Yellow PUR AWM 5 X 22 AWG 300V, 4A -40°C to +80°C 5.8mm OD	Oil and Cutting Fluid Resistant Cut Resistant PUR		
	MDCWF-5MP-**-B	Black TPE AWM 5 X 22 AWG 300V, 4A -40°C to +80°C 5.2mm OD	Hi-Flex Weld Slag Resistant TPE		

** Lengths in meters. Standard cable lengths are 1, 2, 4, 5, 6, 10 & 15 meters. Consult the factory for other lengths.

Standard coupling nut is nickel plated brass, for stainless steel coupling nut add a "-SS" suffix. (e.g. MDC-5MPX-1M becomes MDC-5MPX-1M-SS)