



PART NUMBER	LENGTH "L"
LP3-2GF-DB9-03-RJ45-USB-AFAF	3 FEET
LP3-2GF-DB9-06-RJ45-USB-AFAF	6 FEET
LP3-2GF-DB9-10-RJ45-USB-AFAF	10 FEET

A device employing a 15 A or 20 A grounding type receptacle but no supplementary protector shall be protected by a fuse or circuit breaker that does not exceed the marked rating of the receptacle in the end use. When a fuse or circuit breaker rated less than the receptacle's rating is provided, a Marking shall be provided to indicate the maximum ampere rating of the protection provided.

These devices shall be mounted on enclosures having adequate strength and thickness and with adequate spacing provided. Seal rating is based on mounting to a surface that is clean, flat and smooth.

PIC RATINGS/SPECIFICATIONS	
VOLTS:	125V
AMPS:	15A
SCCR:	10kA
NEMA/UL   EN 60529:	4, 12   IP65
PANEL THICKNESS:	5.0mm max
MOUNTING SCREW TORQUE:	0.8N-m
TERMINAL BLOCK TORQUE:	0.5N-m
INCOMING POWER WIRE SIZE:	0.25 - 2.5 sq mm / 24-12AWG
WIRE STRIP LENGTH:	7 - 8 mm



HOUSING MATERIALS		UNLESS OTHERWISE SPECIFIED:
BODY:	NICKEL PLATED ZINC	
GASKETS:	PUR FIPG	DIMENSIONS ARE IN INCHES AND [MM]
FRONT COVER:	POLYCARBONATE	
LATCH & LOCK:	PBT	
BACK COVER:	POLYPROPYLENE	
PLATE:	304 STAINLESS	

**PROPRIETARY AND CONFIDENTIAL**  
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS PROHIBITED.

DRAWN BY		DCG	<b>MENCOM CORPORATION</b>	
DRAWN DATE		08/17/2018		
CHECKED BY		JJH		
CHECK DATE		08/17/2018		
COMMENTS:			TITLE:	
			CC; 2GF; DB9-ZZ; RJ45; USB-AA; LP3	
SIZE	DWG. NO.	REV		
<b>B</b>	LP3-2GF-DB9-ZZ-RJ45-USB-AFAF	<b>B</b>		
SCALE: 1:2		WEIGHT:	SHEET 1 OF 1	