

Modular Signal Towers / KombiSIGN 72

AndonWirelessSET Basic 2-Button 868MHz



Part No.:	649.000.12
Series:	KombiSIGN 72

MECHANICAL DATA

Housing colour	Black
Type of fixing	Base mounting Tube mounting Wall mounting
Working temperature minimum	0°C
Working temperature maximum	+40°C
Weight with packaging	1273 g
Product weight	1099 g

ELECTRICAL DATA

Operating voltage	115-230V
Operating voltage type	AC
Operating voltage frequency	50Hz at 230V 60Hz at 115V
Operating voltage tolerance	+/- 10%
Rated operational voltage	230 VAC
connectivity	USB

OPTICAL DATA

Light source	LED
Light colour	Green Red
Optical signal image	Blink Permanent TwinLight
Blink frequency (Hz)	1 Hz
Service life optical	50,000 h maximum

APPROVAL DATA

Conforms with CE	No
WEEE	No
Conforms with RED directive	No
Conforms with CCC	No
Conforms with FCC	No
Conforms with IC	No
EAC certificate available	No
Conforms with AS-I	No
Conforms with GL	No
Conforms with VdS	No



For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.