



## TKM/92/9024VDC

- Metal enclosure
- High holding force

## Data

### Ordering data

EAN (European Article Number)	4030661450995
eCl@ss number, Version 9.0	27-27-26-03
eCl@ss number, Version 11.0	27-27-26-03

### Approval - Standards

Certificates	EAC
--------------	-----

### General data

Standards	EN 60947-5-1 EN ISO 13849-1
Coding level according to ISO 14119	Low
Active principle	electromechanical
Enclosure material	Aluminium
Material of the contacts, electrical	Silver
Gross weight	1,400 g

### General data - Features

Number of actuating directions	3
Number of auxiliary contacts	2
Number of safety contacts	2

## Safety appraisal

Standards	EN ISO 13849-1
Mission Time	20 Year(s)

## Safety appraisal - Safety outputs

B10d Normally-closed contact (NC)	2,000,000 Operations
B10d Normally open contact (NO)	1,000,000 Operations

## Mechanical data

Mechanical life, minimum	2,000,000 Operations
Clamping force in accordance with ISO14119 Fzh	4,000 N
Latching force	20 N
Positive break force, minimum	20 N
Actuating speed, maximum	0.3 m/s

## Mechanical data - Connection technique

Terminal Connector	Screw terminals
Cable section, minimum	2 x 0.75 mm <sup>2</sup>
Cable section, maximum	2 x 2.5 mm <sup>2</sup>
Note (Cable section)	All indications about the cable section are including the conductor ferrules.

## Mechanical data - Dimensions

Length of sensor	50 mm
Width of sensor	87 mm
Height of sensor	192 mm

### Ambient conditions

Degree of protection	IP67 to EN 60529
Ambient temperature, minimum	+0 °C
Ambient temperature, maximum	+50 °C

### Ambient conditions - Insulation value

Rated insulation voltage $U_i$	400 V
Rated impulse withstand voltage $U_{imp}$	2.5 kV

### Electrical data

Thermal test current	10 A
Rated control voltage	24 VAC/DC
Electrical power consumption, maximum	10 W
Switching element	NO contact, NC contact
Switching principle	Snap switch element

### Electrical data - Safety contacts

Voltage, Utilisation category AC15	230 VAC
Current, Utilisation category AC-15	8 A
Voltage, Utilisation category DC13	24 VDC
Current, Utilisation category DC13	5 A

### Electrical data - Auxiliary contacts

Voltage, Utilisation category AC15	230 VAC
------------------------------------	---------

