DATASHEET





PS215-T02-K230

- Metal enclosure
- Design to EN 50047
- Quick connection technology as connection terminals rotated by 45°
- Simple and quick to adjust the control elements by 45°.
- cable entry 1 x M20 x 1,5
- Actuation from bottom parallel to the switch, therefore only suitable for small housings.

Data

Ordering data

EAN (European Article Number) 4030661501574

Approval - Standards

Certificates cULus CCC

EAC

General data

Standards IEC 60947-5-1

Housing construction form Norm construction design

Enclosure material Metal, zinc die-cast

Enclosure coating material painted

Material of the contacts, electrical Silver

Gross weight 217.6 g

General data - Features

Safety functions Yes

Number of safety contacts 2

Safety appraisal

Standards EN ISO 13849-1

Mission Time 20 Year(s)

Safety appraisal - Safety outputs

B10d Normally-closed contact (NC) 20,000,000 Operations

Mechanical data

Actuating element Angle roller lever K230

Mechanical life, minimum 10,000,000 Operations

Positive break force, minimum 40 N

Actuating speed, minimum 60 mm/min

Actuating speed, maximum 1 m/s

Mechanical data - Connection technique

Terminal Connector Screw connection

Cable section, minimum 0.34 mm²

Cable section, maximum 1.5 mm²

Mechanical data - Dimensions

Length of sensor 32.5 mm

Width of sensor 31 mm

Height of sensor 93.5 mm

Ambient conditions	
Degree of protection	IP66 IP67
Ambient temperature, minimum	-30 °C
Ambient temperature, maximum	+80 °C

Ambient conditions - Insulation value	
Rated insulation voltage U _i	300 V
Rated impulse withstand voltage U _{imp}	4 kV

Electrical data	
Thermal test current	10 A
Required rated short-circuit current to EN 60947-5-1	400 A
Utilisation category AC-15	240 VAC
Utilisation category AC-15	3 A
Utilisation category DC-13	24 VDC
Utilisation category DC-13	3 A
Switching element	2 NC contact
Switching principle	Creep circuit element
Switching frequency	5,000 /h

Schmersal, Inc., 15 Skyline Drive, Hawthorne, NY 10532

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 11/9/2021, 11:07 AM