



ZR 235-11Z-M20-2325

- with stronger return spring in basic switch
- actuating force $12N \pm 5\%$
- enclosure with round mounting holes $D=5\text{mm}$
- temperature resistant to -40°C
- not applicable for changing temperature
- Metal enclosure
- Wide range of alternative actuators
- Good resistance to oil and petroleum spirit
- $30\text{ mm} \times 63,5\text{ mm} \times 30\text{ mm}$
- Actuator heads can be repositioned by $4 \times 90^{\circ}$
- Mounting details to EN 50047

Data

Ordering data

EAN (European Article Number) 4030661221069

Approval - Standards

Certificates CCC
EAC

General data

Standards IEC 60947-5-1
EN ISO 13849-1
BG-GS-ET-15

Housing construction form Norm construction design

Actuator type to DIN EN 50047 c

Enclosure material Zinc die-cast, paint finish

Material of the contacts, electrical	Silver
Gross weight	155 g

General data - Features

Safety functions	Yes
Number of auxiliary contacts	1
Number of safety contacts	1

Safety appraisal

Standards	EN ISO 13849-1
Mission Time	20 Year(s)

Safety appraisal - Safety outputs

B10d Normally-closed contact (NC)	20,000,000 Operations
-----------------------------------	-----------------------

Mechanical data

Actuating element	Roller plunger
Mechanical life, minimum	20,000,000 Operations
Actuating force, minimum	12 N
Positive break force, minimum	19 N
Actuating speed, minimum	20 mm/min
Actuating speed, maximum	1 m/s

Mechanical data - Connection technique

Terminal Connector	Screw terminals M20 x 1.5
Cable section, minimum	0.75 mm ²
Cable section, maximum	2.5 mm ²

Note (Cable section)

All indications about the cable section are including the conductor ferrules.

Mechanical data - Dimensions

Length of sensor	30 mm
Width of sensor	30 mm
Height of sensor	86 mm

Ambient conditions

Degree of protection	IP65 to EN 60529 IP67 to EN 60529
Ambient temperature, minimum	-40 °C
Ambient temperature, maximum	+80 °C

Ambient conditions - Insulation value

Rated insulation voltage U_i	250 V
Rated impulse withstand voltage U_{imp}	6 kV

Electrical data

Thermal test current	10 A
Required rated short-circuit current to EN 60947-5-1	1,000 A
Utilisation category AC-15	240 VAC
Utilisation category AC-15	4 A
Utilisation category DC-13	24 VDC
Utilisation category DC-13	1 A
Switching element	NO contact, NC contact
Switching principle	Snap switch element
Bounce duration, maximum	3 ms

Switching frequency 5,000 /h

Switchover time, minimum 5.5 ms

Schmersal, Inc., 15 Skyline Drive, Hawthorne, NY 10532

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 11/9/2021, 11:46 AM