



## TS 355-11Z-M20

- 3 cable entries lateral M 20 x 1.5
- Metal enclosure
- Wide range of alternative actuators
- Good resistance to oil and petroleum spirit
- 66,7 mm x 76 mm x 38 mm
- Actuator heads can be repositioned by 4 x 90°
- Mounting details to EN 50041
- Switching points to EN 50041

## Data

### Ordering data

EAN (European Article Number)	4030661294964
eCl@ss number, Version 9.0	27-27-26-01
eCl@ss number, Version 11.0	27-27-26-01
ETIM number, version 6.0	EC000030
ETIM number, version 7.0	EC000030

### Approval - Standards

Certificates	cULus CCC EAC
--------------	---------------------

### General data

Housing construction form	Norm construction design
Actuator type to DIN EN 50041	B

Enclosure material	Aluminium
Enclosure coating material	painted
Material of the contacts, electrical	Silver
Gross weight	230 g

### General data - Features

Safety functions	Yes
Number of auxiliary contacts	1
Number of safety contacts	1

### Safety appraisal

Standards	EN ISO 13849-1
Mission Time	20 Year(s)

### Safety appraisal - Safety outputs

B10d Normally-closed contact (NC)	20,000,000 Operations
B10d Normally open contact (NO)	1,000,000 Operations

### Mechanical data

Actuating element	Plunger
Mechanical life, minimum	30,000,000 Operations
Actuating force, minimum	17 N
Actuating speed, maximum	0.5 m/s
Note (Switchover time)	Switchover time in accordance with actuating speed

### Mechanical data - Connection technique

Terminal Connector	Screw connection
Cable section, minimum	0.75 mm <sup>2</sup>

Cable section, maximum	2.5 mm <sup>2</sup>
Note (Cable section)	All indications about the cable section are including the conductor ferrules.

### Mechanical data - Dimensions

Length of sensor	38 mm
Width of sensor	66.7 mm
Height of sensor	103.5 mm

### Ambient conditions

Degree of protection	IP65 to EN 60529 IP67 to EN 60529
Ambient temperature, minimum	-30 °C
Ambient temperature, maximum	+80 °C

### Ambient conditions - Insulation value

Rated insulation voltage $U_i$	500 V
Rated impulse withstand voltage $U_{imp}$	6 kV

### Electrical data

Thermal test current	10 A
Required rated short-circuit current to EN 60947-5-1	1,000 A
Utilisation category AC-15	230 VAC
Utilisation category AC-15	4 A
Utilisation category DC-13	24 VDC
Utilisation category DC-13	4 A
Switching element	NO contact, NC contact
Switching principle	Slow action

Bounce duration, maximum	2 ms
Switching frequency	5,000 /h

Schmersal, Inc., 15 Skyline Drive, Hawthorne, NY 10532

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 11/9/2021, 9:55 AM