



CSS 8-180-2P-Y-L

- 2 x Pre-wired cable 4-pole
- Thermoplastic enclosure
- Electronic contact-free, coded system
- Misaligned actuation possible
- High repeat accuracy of the switching points
- Max. length of the sensor chain 200 m
- Early warning when operating near the limit of the sensor's hysteresis range
- Self-monitoring series-wiring of 16 sensors
- 2 short-circuit proof PNP safety outputs

Data

Ordering data

EAN (European Article Number)	4030661208787
eCl@ss number, Version 9.0	27-27-24-03
eCl@ss number, Version 11.0	27-27-24-03

Approval - Standards

Certificates	cULus EAC
--------------	--------------

General data

Standards	IEC 61508 IEC 60947-5-3
Active principle	inductive

Housing construction form	Cylinder, thread
Installation conditions (mechanical)	not flush
Sensor topology	Sensor for series wiring
Enclosure material	Glass-fibre, reinforced thermoplastic
Active area	Glass-fibre, reinforced thermoplastic
Material of the nuts	Glass-fibre, reinforced thermoplastic
Gross weight	167 g
Reaction time, maximum	30 ms
Duration of risk, maximum	30 ms

General data - Features

Short circuit detection	Yes
Short-circuit recognition	Yes
Safety functions	Yes
Cascadable	Yes
Integral System Diagnostics, status	Yes
Number of fail-safe digital outputs	2
Number of Series-wiring of sensors	16

Safety appraisal

Standards	EN ISO 13849-1 IEC 60947-5-3 IEC 61508
Performance level, up to	e
Control category to EN13849	4
PFH-value	2.50×10^{-9} /h
Safety Integrity Level (SIL), suitable for applications in	3

Mission Time	20 Year(s)
--------------	------------

Mechanical data

Hysteresis (Switch distance), maximum	0.7 mm
---------------------------------------	--------

Repeat accuracy R R	0.2 mm
---------------------	--------

Tightening torque of nuts, maximum	3 Nm
------------------------------------	------

Mechanical data - Switching distances according IEC 60947-5-3

Switch distance	8 mm
-----------------	------

Ensured switch distance "ON" S_{ao}	7 mm
--	------

Ensured switch distance "OFF" S_{ar}	10 mm
---	-------

Mechanical data - Connection technique

Terminal Connector	Cable
--------------------	-------

Terminal connector, Input	4-pole
---------------------------	--------

Terminal connector, Output	4-pole
----------------------------	--------

Mechanical data - Dimensions

ISO thread of the sensor	M18
--------------------------	-----

width across flats	24 BK
--------------------	-------

Length of sensor	92 mm
------------------	-------

Ambient conditions

Degree of protection	IP65 to EN 60529 IP67 to EN 60529
----------------------	--------------------------------------

Ambient temperature, minimum	-25 °C
Ambient temperature, maximum	+60 °C
Storage and transport temperature, minimum	-25 °C
Storage and transport temperature, maximum	+85 °C
Resistance to vibrations to EN 60068-2-6	10 ... 55 Hz, amplitude 1 mm
Resistance to shock	30 g / 11 ms
Protection rating	II

Ambient conditions - Insulation value

Rated insulation voltage U_i	32 VDC
Rated impulse withstand voltage U_{imp}	0.8 kV
Overvoltage category	III
Degree of pollution to VDE 0100	3

Electrical data

Voltage type	DC (direct current)
Operating voltage, minimum	20.4 VDC
Operating voltage, maximum	26.4 VDC
No-load supply current I_0	50 mA
Rated operating voltage	24 VDC
Operating current	1,000 mA
Switching frequency, approx.	3 Hz

Electrical data - Fail-safe digital outputs

Rated operating current (safety outputs)	500 mA
Output current, (fail-safe output), maximum	0.5 A
Versions	p-type
Voltage drop U_d , maximum	0.5 V
Current leakage I_r	0.5 mA
Voltage, Utilisation category DC12	24 VDC
Current, Utilisation category DC12	0.5 A
Voltage, Utilisation category DC13	24 VDC
Current, Utilisation category DC13	0.5 A

Status indication

Note (LED switching conditions display)	Multi-coloured LED: Green, Red, Yellow
--	--

Pin assignment

PIN 1	A1 Ue Brown
PIN 2	Y2 safety output 2, X2 safety input 2: White
PIN 3	A2 GND
PIN 4	Y1 safety output 1, X1 safety input 1: Black

Scope of delivery

Included in delivery	Actuators must be ordered separately.
Delivery scope of Mounting material	2x nuts M18 x 1

Accessory

Recommendation (actuator)	CST 180-1 CST 180-2
Recommended safety switchgear	PROTECT PSC1 SRB-E-301ST SRB-E-201LC

Notes

Note (General)	Evaluation requirements: dual-channel safety input, suitable for p-type sensors with NO function. The safety-monitoring module must tolerate internal functional tests of the sensors with cyclic switch-off of the sensor outputs for max. 0.25 ms. Short-circuit recognition by the evaluation is not necessary.
----------------	--

Schmersal, Inc., 15 Skyline Drive, Hawthorne, NY 10532

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 11/9/2021, 10:45 AM