



## BNS 260-11/01ZG-R

- Pre-wired cable
- Thermoplastic enclosure
- Small body
- Concealed mounting possible
- 26 mm x 36 mm x 13 mm
- Long life
- no mechanical wear
- Insensitive to transverse misalignment
- Insensitive to soiling

## Data

### Ordering data

EAN (European Article Number)	4030661321745
eCl@ss number, Version 9.0	27-27-24-02
eCl@ss number, Version 11.0	27-27-24-02
ETIM number, version 6.0	EC002544
ETIM number, version 7.0	EC002544

### Approval - Standards

Certificates	TÜV
	BG
	cULus
	EAC

### General data

Standards	IEC 60947-5-3 BG-GS-ET-14
Coding level according to ISO 14119	Low
Active principle	Magnetic drive
Installation conditions (mechanical)	quasi-flush
Enclosure material	Glass-fibre, reinforced thermoplastic
Gross weight	60 g

### General data - Features

Integral System Diagnostics, status	Yes
Number of openers	2
Number of shutters	1
Number of safety contacts	2
Number of cable wires	6

### Safety appraisal

Standards	EN ISO 13849-1
Mission Time	20 Year(s)

### Safety appraisal - Safety outputs

B10d- Value Normally-closed contact/Normally open contact (NC/NO)	25,000,000 Operations
---	-----------------------

### Mechanical data

Actuating element	Magnet
Door hinge	Right

Direction of motion

Head-on to the active surface

### Mechanical data - Switching distances according IEC 60947-5-3

Notice (Switch distance $S_n$ )	Axial misalignment, a horizontal and vertical misalignment of the safety sensor and the actuator are tolerated. The possible misalignment depends on the distance of the active surfaces of the sensor and the actuator. The sensor remains active within the tolerance range.	
Ensured switch distance "ON" $S_{ao}$	5 mm	
Ensured switch distance "OFF" $S_{ar}$	15 mm	

### Mechanical data - Connection technique

Terminal Connector	Cable
Length of cable	1 m
Wire cross-section	0.25 mm <sup>2</sup>
Material of the Cable mantle	PVC

### Mechanical data - Dimensions

Length of sensor	13 mm
Width of sensor	26 mm
Height of sensor	36 mm

### Ambient conditions

Degree of protection	IP67
Ambient temperature, minimum	-25 °C
Ambient temperature, maximum	+70 °C
Storage and transport temperature, minimum	-25 °C
Storage and transport temperature, maximum	+70 °C

Resistance to vibrations to EN 60068-2-6	10 ... 55 Hz, amplitude 1 mm
--	------------------------------

Resistance to shock	30 g / 11 ms
---------------------	--------------

## Electrical data

Voltage type	DC (direct current)
--------------	---------------------

Switching voltage, maximum	24 VDC
----------------------------	--------

Switching current, maximum	0.01 A
----------------------------	--------

Switching capacity, maximum	0.2 W
-----------------------------	-------

Switching frequency, maximum	5 Hz
------------------------------	------

## Status indication

Note (Integral System Diagnostics, status )	The LED is illuminated when the guard is closed.
---	--

## Scope of delivery

Included in delivery	Actuators must be ordered separately.
----------------------	---------------------------------------

## Accessory

Recommendation (actuator)	BPS 260
---------------------------	---------

Recommended safety switchgear	SRB-E-301ST SRB-E-201LC
-------------------------------	----------------------------

## Notes

Note (General)	Contact symbols shown for the closed condition of the guard device. The contact configuration for versions with or without LED is identical.
----------------	---

Schmersal, Inc., 15 Skyline Drive, Hawthorne, NY 10532

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 11/9/2021, 11:22 AM