



## KA-0974

- Pre-wired cable
- 8-pole
- for SLC/SLG

## Data

### Ordering data

EAN (European Article Number)	4030661412863
eCl@ss number, Version 9.0	27-27-27-92
eCl@ss number, Version 11.0	27-27-27-92

### General data

Connector (electric)	Female connector
Gross weight	107 g

### General data - Features

Halogen free	No (0)
Cable drag chain suitable	No (0)
Number of poles	8
Number of cable wires	3

### Mechanical data

Tightening torque, maximum	1 Nm
----------------------------	------

### **Mechanical data - Connection technique**

Length of cable	1 m
Wire cross-section	0.34 mm <sup>2</sup>
Colour of the Cable mantle	Grey
Material of the Cable mantle	PVC

### **Mechanical data - connector side A**

Connector typ	Female connector, M12
Design	straight
Connector latching	Screw locking
Material of the gland	Metal, CuZn, nickel-plated
Material of the handle	Plastic, TPU
Colour of the handle	Black

### **Mechanical data - connector side B**

Connector typ	Male connector, M12
Design	straight
Connector latching	Screw locking
Material of the gland	Metal, CuZn, nickel-plated
Material of the handle	Plastic, TPU

### **Mechanical data - Dimensions**

Diameter of the ISO-thread	M12
----------------------------	-----

### **Ambient conditions**

Degree of protection	IP67
Ambient temperature, minimum	-30 °C

Ambient temperature, maximum	+90 °C
------------------------------	--------

## Electrical data

Thermal test current	2 A
Rated operating voltage	60 V
Operating current	2,000 mA

## Notes

Note (General)	Parameterization cable for SLC/SLG 440 with push-button
----------------	---

Schmersal, Inc., 15 Skyline Drive, Hawthorne, NY 10532

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 11/9/2021, 10:38 AM