



SEP-K02.0.4.0.22/95

- Thermoplastic enclosure
- 2 black operating buttons (positioning parts) Ø 55
- 1 Emergency Stop button in thermoplastic version
- Stand and wall mounting possible
- 2 part enclosure

Data

Ordering data

EAN (European Article Number)	4250116202812
eCl@ss number, Version 9.0	27-37-12-19
eCl@ss number, Version 11.0	27-37-12-19
ETIM number, version 6.0	EC001260

Approval - Standards

Certificates	cULus EAC
--------------	--------------

General data

Standards	EN ISO 13850 IEC/EN 60947-5-5 EN ISO 13851
Enclosure material	Plastic
Gross weight	1,900 g

General data - Features

Construction kit possible	Yes
Suitable for EMERGENCY-OFF	Yes
Number of Emergency Stop button	1
Number of openers	1
Number of shutters	1
Number of operating push buttons (positioning parts)	2

Mechanical data

Mechanical life, minimum	10,000,000 Operations
--------------------------	-----------------------

Mechanical data - Connection technique

Terminal Connector	Screw connection
Cable section, maximum	1.5 mm ²

Mechanical data - Dimensions

Width	469 mm
Height	185 mm
Depth	137 mm
Length x Width x Height	Operating push buttons (positioning parts): 55 mm Emergency stop pushbutton: 38.5 mm

Ambient conditions

Degree of protection	IP65
----------------------	------

Ambient conditions - Insulation value

Rated insulation voltage U_i	440 V
--------------------------------	-------

Electrical data

Thermal test current	10 A
Utilisation category AC-15	250 VAC
Utilisation category AC-15	8 A
Utilisation category DC-13	24 VDC
Utilisation category DC-13	5 A

Accessory

Recommendation (product combination)	SRB201ZH SRB200ZHX1 SRB 201ZHX3
--------------------------------------	---------------------------------------

Notes

Note (General)	1 NO/1 NC contact per unit, 1 NO/1 NC contact for Emergency-Stop Optional: actuators with low actuating force 8 knockouts for additional operating devices Ø 22.3 mm
----------------	---

Schmersal, Inc., 15 Skyline Drive, Hawthorne, NY 10532

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 11/9/2021, 10:38 AM