



SLG445-ER-0500-02-01

- Safety type 4 in accordance with IEC 61496-1
- User-friendly parameter setting, no tools required
- Reliable safety concept in case of interferences (EMC, welding sparks)
- Process safety with highest availability
- active integrated set-up tool
- 

Data

Ordering data

EAN (European Article Number)	4030661436388
eCl@ss number, Version 9.0	27-27-27-03
eCl@ss number, Version 11.0	27-27-27-03

Approval - Standards

Certificates	TÜV cULus EAC
--------------	---------------------

General data

Standards	EN 61496-1 EN 61496-2 CLC/TS 61496-2
Enclosure material	Aluminium
Gross weight	980 g
Reaction time, maximum	10 ms

General data - Features

Muting function	Yes
Override	Yes
Clock control possible	Yes
Restart interlock (manual reset)	Yes
Beam coding available	Yes
7-segment display	Yes
Integral System Diagnostics, status	Yes
Integral System Diagnostics	Yes
Number of beams	2
Number of fail-safe digital outputs	2

Safety appraisal

Standards	EN ISO 13849-1 EN 62061
Performance level, up to	e
Control category to EN13849	4
PFH-value	5.14×10^{-9} /h
Safety Integrity Level (SIL), suitable for applications in	3
Mission Time	20 Year(s)
Safety type in accordance with IEC 61496-1	4

Mechanical data

Detection ability for test bodies at $v = 1.6$ m/s	500 mm
Height of the protection field	500 mm
Range, protection field, minimum	300 mm
Range, protection field, maximum	12,000 mm

Wave length of the sensor	880 nm
---------------------------	--------

Mechanical data - Connection technique

Terminal Connector	Connector
Length of cable	100 m
Terminal connector, Recipient	Connector plug M12, 12-pole
Terminal, Connector, Transmitter	Connector plug M12, 4-pole

Mechanical data - Dimensions

Length of sensor	33 mm
Width of sensor	27.8 mm
Height of the Sensor (Receiver)	621 mm
Height of the Sensor (Transmitter)	611 mm

Ambient conditions

Degree of protection	IP67 to EN 60529
Ambient temperature, minimum	-25 °C
Ambient temperature, maximum	+50 °C
Storage and transport temperature, minimum	-25 °C
Storage and transport temperature, maximum	+70 °C
Protection rating	III

Electrical data

Voltage type	DC (direct current)
Switching voltage OSSD, HIGH signal	24 V
Electrical power consumption of the receiver, maximum	10 W
Electrical power consumption of the transmitter, maximum	5 W

Length of cable, maximum	100 m
--------------------------	-------

Electrical data - Fail-safe digital outputs

Output current, (fail-safe output), maximum	0.25 A
---	--------

Versions	p-type
----------	--------

Scope of delivery

Included in delivery	Kit with 2 mounting angles
----------------------	----------------------------

Accessory

Recommended safety switchgear	SRB-E 301
-------------------------------	-----------

Notes

Note (General)	I_m In case of failure (interruption of the 0 V supply) the maximum leakage current is 1 mA.
----------------	--

Schmersal, Inc., 15 Skyline Drive, Hawthorne, NY 10532

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 11/9/2021, 10:27 AM