



AZ201-I1-ST-T-AS

- Safety switch with separate actuator
- Thermoplastic enclosure
- Integrated AS-Interface
- 40 mm x 220 mm x 50 mm
- 3 LEDs to show operating conditions
- Sensor technology permits an offset between actuator and interlock of ± 5 mm vertically and ± 3 mm horizontally
- Intelligent diagnosis
- With door detection sensor T
- Protection class IP67

Data

Ordering data

EAN (European Article Number)	4030661524368
eCl@ss number, Version 9.0	27-27-26-02
eCl@ss number, Version 11.0	27-27-26-02

Approval - Standards

Certificates	TÜV
	cULus
	ASi-SaW
	EAC
	FCC
	IC

General data

Standards	EN ISO 13849-1 IEC 61508 IEC 60947-5-3 EN ISO 14119 IEC 62061 EN 62026-2
general information	Individual coding
Coding level according to ISO 14119	High
Active principle	RFID
Enclosure material	Glass-fibre, reinforced thermoplastic
Gross weight	351 g
Time to readiness, maximum	4,000 ms
Reaction time, maximum	100 ms
Duration of risk, maximum	200 ms

General data - Features

Latching	Yes
Safety functions	Yes
Integral System Diagnostics, status	Yes
Number of actuating directions	2

Safety appraisal

Standards	IEC 62061 IEC 61508 EN ISO 13849-1
-----------	--

Safety appraisal - Interlocking

Performance level, up to	e
Control category	4
PFH-value	$1.81 \times 10^{-9} /h$
PFD value	1.59×10^{-4}

Safety Integrity Level (SIL), suitable for applications in	3
Mission Time	20 Year(s)

Mechanical data

Mechanical life, minimum	1,000,000 Operations
Latching force	30 N
Actuating speed, maximum	0.2 m/s
Tightening torque for the fixing screws, maximum	8 Nm

Mechanical data - Connection technique

Terminal Connector	Connector plug M12, 4-pole, (A-coding)
--------------------	--

Mechanical data - Dimensions

Length of sensor	50 mm
Width of sensor	40 mm
Height of sensor	220 mm

Ambient conditions

Degree of protection	IP66 to EN 60529 IP67 to EN 60529
Ambient temperature, minimum	-25 °C
Ambient temperature, maximum	+65 °C
Storage and transport temperature, minimum	-25 °C
Storage and transport temperature, maximum	+85 °C
Relative humidity, minimum	10 %
Relative humidity, maximum	95 %

Note (Relative humidity)	non-condensing non-icing
Resistance to vibrations to EN 60068-2-6	10 ... 150 Hz, amplitude 0.35 mm
Resistance to shock	30 g / 11 ms
Protection rating	III

Ambient conditions - Insulation value

Rated insulation voltage U_i	32 VDC
Rated impulse withstand voltage U_{imp}	0.8 kV
Overvoltage category	III
Degree of pollution to IEC/EN 60664-1	3

Electrical data

Switching frequency, maximum	1 Hz
------------------------------	------

Electrical data - AS Interface

AS-i Operating voltage, minimum	26.5 VDC
AS-i Operating voltage AS-i maximum	31.6 VDC
Note (AS-i Operating voltage)	Protection against polarity reversal
AS-i Current consumption, maximum	100 mA

Electrical data - AS-Interface specification

AS-i Specification	Safety-Slave
AS-i Version	V 3.0
AS-i Profile	S-0.B.F.E
AS-i, IO-Code	0x0
AS-i, ID-Code	0xB
AS-i, ID-Code1	0xF
AS-i, ID-Code2	0xE

AS-i Input, Channel 1	Data bits DI 0 / DI 1 = dynamic code transmission
AS-i Input, Channel 2	Data bits DI 2 / DI 3 = dynamic code transmission
AS-i Outputs, DO 0	No Function
AS-i Outputs, DO 1	No Function
AS-i Outputs, DO 2	No Function
AS-i Outputs, DO 3	No Function
AS-i Parameter bits, P0	Safety guard and actuator detected
AS-i Parameter bits, P1	Static 0
AS-i Parameter bits, P3	Internal device error (FID)
Note (AS-i Parameter bits)	FID: periphery error
AS-i AS-i Parameter bits (A/B Slave), P2	Enabling inhibit (tamper protection time) active (FID)
AS-i Input module address	0
Note (AS-i Input module address)	Preset to address 0, can be changed through AS-interface bus master or hand-held programming device

Status indication

Note (LED switching conditions display)	Status and diagnostics: Transmitter + receiver (2) LED red: Internal device error (3) LED yellow: Device condition
---	--

Pin assignment

PIN 1	AS-Interface +
PIN 2	n.c.
PIN 3	AS-Interface -
PIN 4	n.c.

Scope of delivery

Included in delivery	Actuators must be ordered separately.
----------------------	---------------------------------------

Accessory

Recommendation (actuator)	AZ/AZM201-B1 AZ/AZM201-B30
---------------------------	-------------------------------

Schmersal, Inc., 15 Skyline Drive, Hawthorne, NY 10532

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 11/9/2021, 11:13 AM