



## SEPG05.3.L.22

- Metal enclosure
- without mountings with 3 mounting holes Ø 22.3 mm
- 2 part enclosure
- Stand and wall mounting possible
- light alloy die-casting
- Ergonomic operation
- The terminal blocks and relay can be mounted in the inner part
- Operating panel suitable for at least 8 additional command devices and indicator lights
- Holes drilled under the cover and central hole Ø = 22,3mm

## Data

### Ordering data

EAN (European Article Number)	4250116202911
eCl@ss number, Version 9.0	27-37-12-19
eCl@ss number, Version 11.0	27-37-12-19
ETIM number, version 6.0	EC001260

### General data

Standards	EN ISO 13850 IEC/EN 60947-5-5 EN ISO 13851
Enclosure material	Aluminium
Enclosure coating material	powder-coated
Gross weight	4,430 g



## General data - Features

Suitable for EMERGENCY-OFF	Yes
----------------------------	-----

## Mechanical data - Dimensions

Width	494 mm
-------	--------

Height	184 mm
--------	--------

Depth	160 mm
-------	--------

## Ambient conditions

Degree of protection	IP65
----------------------	------

## Notes

Note (General)	Optional: actuators with low actuating force Central part suitable for fitting of up to 10 additional command devices and indicator lights (Ø 22 mm)
----------------	---

Schmersal, Inc., 15 Skyline Drive, Hawthorne, NY 10532

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 11/9/2021, 10:40 AM