



SD-I-DP-V0-2 PROFIBUS-GATEWAY

- PROFIBUS Gateway SD-I-DP-V0-2 to convert serial diagnostic signals to the PROFIBUS DP protocol
- The PROFIBUS Gateway SD-I-DP-V0-2 is a PROFIBUS slave
- Protection class IP 10 device for control cabinet mounting, for standard DIN rails

Data

Ordering data

EAN (European Article Number) 4030661353951

eCl@ss number, Version 9.0 27-23-02-08

General data

Gross weight 120 g

General data - Features

Integral System Diagnostics, status Yes

Number of LEDs 4

Mechanical data

Mounting Snaps onto standard DIN rail to EN 60715

Mechanical data - Connection technique

Mechanical data - Dimensions

Width 50 mm

Height 72 mm

Depth 97 mm

Ambient conditions

Degree of protection of the enclosure IP10

Ambient temperature, minimum -5 °C

Ambient temperature, maximum +55 °C

Storage and transport temperature, -25 °C

minimum

Storage and transport temperature,

maximum

Resistance to vibrations to EN 60068-2-6 5 ... 9 Hz, Amplitude 3.5 mm

9 ... 150 Hz, with 1 g

+85 °C

Restistance to shock 15 g / 11 ms

Ambient conditions - Insulation value

Rated insulation voltage U_i 32 V

Rated impulse withstand voltage U_{imp} 0.5 kV

Overvoltage category II

Degree of pollution to VDE 0110 2

Electrical data

Rated operating voltage 24 VDC, - 15 % / + 20 % (stabilised PELV)

Operating current 250 mA

Status indication

Note (LED switching conditions display)

ON permanent light green: supply voltage present

PB Flashing signal: PROFIBUS initialisation
PB Permanent light red: PROFIBUS error

SD Flashing signal: = SD gateway initialisation SD Permanent light Red: = SD Gateway fault

Other data

Note (applications)

Safety sensor

Guard system

Notes

Note (General) Detailed functions, see programming and configuration manual of the

SD Gateway

Circuit example

Note (Wiring diagram) Serial diagnostics of series-wired safety sensors/solenoid interlocks

Devices with serial diagnostic option: AZ 200, AZM 200, CSS 30S, CSS

34, MZM 100

Schmersal, Inc., 15 Skyline Drive, Hawthorne, NY 10532

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 11/9/2021, 9:57 AM