



## NWS32.1

### Data

#### Ordering data

EAN (European Article Number)	4250116200382
eCl@ss number, Version 9.0	27-37-12-13
eCl@ss number, Version 11.0	27-37-12-13
ETIM number, version 6.0	EC000222

#### Approval - Standards

Certificates	BG cULus CCC IPA
--------------	---------------------------

#### General data

Standards	EN 60947-5-1 IEC/EN 60947-1
Versions	Selector switch - Front plate mounting
Toggle	long

Sealing type	Membrane Lip gaskets
Material of the operators	ABS
Material of the front ring	ABS, chrome-plated
Colour of the front ring	Silver
Colour of the handle	Grey
Gross weight	35 g

## General data - Features

Latching	Yes
Fully insulated	Yes
Number of plunger	2
Number of switch positions	3

## Mechanical data

Unlocking	Rotating unlatcher
Latching position	right left
Switching angle, left	55 °
Switching angle, right	55 °
Mounting	Mounting flange EFM
Tightening torque of the screw	0.6 Nm

## Mechanical data - Dimensions

Height	11 mm
diameters for the actuating heads	44.5 mm
Length of the handle	46 mm
Diameter hole	22.3 mm
Diameter hole, with tolerance indication	22.3 + 0.4 mm

Thickness, of the front panel, minimum	1.5 mm
Thickness of the front panel, maximum	6 mm
Spacing	50 x 60 mm

## Ambient conditions

Degree of protection	IP67 IP69K
Ambient temperature, minimum	+0 °C
Ambient temperature, maximum	+80 °C

Schmersal, Inc., 15 Skyline Drive, Hawthorne, NY 10532

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 11/9/2021, 9:17 AM