



PROTECT-SELECT-CC

- Simple and flexible parameter setting
- No programming skills required
- 18 safe inputs for the redundant inquiry of all common safety sensors
- 4 safety semi-conductor outputs
- 2 safety relay outputs
- 4 optional signalling outputs
- Replaces up to 8 safety-monitoring modules up to PL e / SIL 3
- Error and status messages in plain text
- Multilingual menu navigation via colour display

Data

Ordering data

EAN (European Article Number)	4030661445403
eCl@ss number, Version 9.0	27-37-18-19
eCl@ss number, Version 11.0	27-37-18-19
ETIM number, version 6.0	EC001449

Approval - Standards

Certificates	TÜV cULus CCC EAC
--------------	----------------------------

General data

Standards	EN ISO 13849-1 IEC 61508 EN 60947-5-1 EN 60204-1 EN 62061
Climatic stress	EN 60068-2-1 EN 60068-2-2 EN 61496
Terminal (mechanical)	Removable cage terminals
Enclosure material	Polyamide / V0
Material of the contacts, electrical	Tin
Gross weight	300 g

General data - Features

Short circuit detection	Yes
Wire breakage detection	Yes
Short-circuit recognition	Yes
Removable Terminals	Yes
Start input	Yes
Feedback circuit	Yes
Automatic reset function	Yes
Reset edge detection	Yes
Start-up test	Yes
Earth connection detection	Yes
Integral System Diagnostics, status	Yes
Integrated Display, Supply Voltage	Yes
Number of pulse outputs (test pulse output)	3
Number of relay outputs (1-channel)	2
Number of fail-safe analogue inputs	2
Number of digital fail-safe inputs	14
Number of digital fail-safe in-/outputs	4
Number of fail-safe digital outputs	4

Number of signalling outputs	4
------------------------------	---

Safety appraisal

Standards	EN 60947-5-1 EN 62061 IEC 61508 EN ISO 13849-1
Performance level, up to	e
Control category to EN13849	4
Diagnostic Coverage (DC) Level	90
PFH-value	1.78×10^{-8} /h
Safety Integrity Level (SIL), suitable for applications in	3
Mission Time	20 Year(s)
Common Cause Failure (CCF), minimum	65
Hardware fault tolerance (HFT)	1
Demand rate	high or continuous
Safe Failure Fraction (SFF), minimum	90

Safety appraisal - Relay outputs

Performance Level, up to	e
Control category to EN13849	4
Notice	Valid for dual channel and 60% relay load
Safety Integrity Level (SIL), suitable for applications in	3

Safety appraisal - Safety inputs 2-channels

Performance level, up to	e
Control category	4
Safety Integrity Level (SIL), suitable for applications in	3

Safety appraisal - Safety inputs 1-channel

Performance level, up to	d
Control category	2
Safety Integrity Level (SIL), suitable for applications in	2

Safety appraisal - Safety outputs 1-channel

Performance level, up to	d
Control category	2
Safety Integrity Level (SIL), suitable for applications in	2

Safety appraisal - Safety outputs 2-channels

Performance level, up to	e
Control category	4
Safety Integrity Level (SIL), suitable for applications in	3

Mechanical data

Mechanical life, minimum	10,000,000 Operations
Mounting	Snaps onto standard DIN rail to EN 60715

Mechanical data - Connection technique

Terminal Connector	rigid or flexible
Terminal designations	IEC 61131-2 IEC/EN 60947-1
Cable section, minimum	0.25 mm ²
Cable section, maximum	2.5 mm ²

Mechanical data - Dimensions

Width	52.5 mm
Height	100 mm
Depth	118 mm

Ambient conditions

Degree of protection	IP20
Degree of protection of the mounting space	IP54
Ambient temperature, minimum	-25 °C
Ambient temperature, maximum	+55 °C
Storage and transport temperature, minimum	-25 °C
Storage and transport temperature, maximum	+75 °C
Relative humidity, minimum	15 %
Relative humidity, maximum	90 %
Note (Relative humidity)	non-condensing
Resistance to vibrations to EN 60068-2-6	10 ... 57 Hz, amplitude 0.75 mm
Resistance to shock	30 g / 11 ms

Ambient conditions - Insulation value

Overvoltage category	III
Degree of pollution to VDE 0100	2

Electrical data

Voltage type	DC (direct current)
Operating voltage	24 V
Operating voltage, minimum	21.6 VDC
Operating voltage, maximum	26.4 VDC
Current consumption at 24V, maximum	500 mA
No-load supply current I_0	500 mA
Required rated short-circuit current to EN 60947-5-1	1,000 A

Switching frequency, maximum	0.1 Hz
------------------------------	--------

Electrical data - Fail-safe digital inputs

Switching thresholds	-3 V ... 2 V (LOW) 18 V ... 28.8 V
Current consumption at 24V	6 mA

Electrical data - Fail-safe digital outputs

Rated operating current (safety outputs)	700 mA
Versions	short-circuit proof, p-type / n-type (Q0/0N and Q1/1N) short-circuit proof, p-type (Q2 und Q3)
Current leakage I_r	2 mA

Electrical data - Safe relay outputs

Voltage, Utilisation category AC1	250 VAC
Current, Utilisation category AC-1	4 A
Voltage, Utilisation category DC1	24 VDC
Current, Utilisation category DC1	4 A
Voltage, Utilisation category AC15	230 VAC
Current, Utilisation category AC-15	3 A
Voltage, Utilisation category DC13	24 VDC
Current, Utilisation category DC13	4 A

Electrical data - Diagnostic output

Operating current	100 mA
Versions	Limited short-circuit protection, p-type

Electrical data - Electromagnetic compatibility (EMC)

Other data

Note (applications)	Safety sensor
	Guard system
	Emergency-Stop button
	Pull-wire emergency stop switches
	Safety light curtain

Schmersal, Inc., 15 Skyline Drive, Hawthorne, NY 10532

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 11/9/2021, 9:15 AM