



## NMLWS

- flat dome
- for Ba9S LED's

## Data

### Ordering data

EAN (European Article Number)	4250116201426
eCl@ss number, Version 9.0	27-37-12-11
eCl@ss number, Version 11.0	27-37-12-11
ETIM number, version 6.0	EC000223

### Approval - Standards

Certificates	BG cULus IPA
--------------	--------------------

### General data

Standards	EN 60947-5-1 IEC/EN 60947-1
Versions	LED - Indicator light - Front plate mounting
Design	Round Flat dome
Installation conditions (mechanical)	arbitrarily

Sealing type	Membrane Lip gaskets Form seals
Material of the dome	PA (12)
Material of the front ring	ABS, chrome-plated
Colour of the dome	White
Colour of the front ring	Silver
Gross weight	30 g

## General data - Features

Illuminable	Yes
Mounting flange	Yes
Fully insulated	Yes

## Mechanical data

Mounting	Mounting flange ELM
Tightening torque of the screw	0.6 Nm

## Mechanical data - Dimensions

Diameter total	44.5 mm
Height of the dome	2 mm
Diameter of the dome	26 mm
Diameter hole	22.3 mm
Diameter hole, with tolerance indication	22.3 + 0.4 mm
Thickness, of the front panel, minimum	1.5 mm
Thickness of the front panel, maximum	6 mm
Spacing	50 x 50 mm

## Ambient conditions

Degree of protection	IP67 IP69K
Ambient temperature, minimum	-25 °C
Ambient temperature, maximum	+80 °C

### Status indication

Note (Integral System Diagnostics, status )	for 24 VAC/DC
---	---------------

### Scope of delivery

Note (included in delivery, number and type)	Mounting flange ELM is included in delivery
--	---

Schmersal, Inc., 15 Skyline Drive, Hawthorne, NY 10532

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 11/9/2021, 8:53 AM