



ELDE.NRT230

- Screw connection
- Mounting flange position 3
- red LED
- 230 VAC

Data

Ordering data

EAN (European Article Number)	4250116200818
eCl@ss number, Version 9.0	27-37-12-09
eCl@ss number, Version 11.0	27-37-12-09
ETIM number, version 6.0	EC000204

Approval - Standards

Certificates	cULus
	CCC
	EAC

General data

Standards	EN 60947-5-1 IEC/EN 60947-1
Installation conditions (mechanical)	arbitrarily
Enclosure material	Plastic, glass-fibre reinforced thermoplastic, self-extinguishing
Gross weight	25 g

General data - Features

Integral System Diagnostics, general	Yes
--------------------------------------	-----

Mechanical data

Installation instructions	pluggable
Mounting flange position	3

Mechanical data - Connection technique

Terminal Connector	Screw connection
Terminal designations	EN 50005 EN 50013
Cable section, minimum	0.5 mm ² , rigid 0.5 mm ² , flexible
Cable section, maximum	2.5 mm ² , rigid 1.5 mm ² , flexible

Mechanical data - Dimensions

Length	46 mm
Width	30 mm
Depth	60 mm

Ambient conditions

Degree of protection of clips or terminals	IP20
Ambient temperature, minimum	-25 °C
Ambient temperature, maximum	+80 °C

Ambient conditions - Insulation value

Rated insulation voltage U_i	440 V
--------------------------------	-------

Electrical data

Rated operating voltage	250 V
-------------------------	-------

Status indication

Colour of the LED	Red
Note (LED switching conditions display)	Supply voltage UB: 230 VAC

Schmersal, Inc., 15 Skyline Drive, Hawthorne, NY 10532
The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.
Generated on: 11/9/2021, 10:21 AM