



TR 461-22Y

- 2 cable entries M 20 x 1.5
- Metal enclosure
- 118 mm x 155 mm x 64 mm (basic component)
- Actuator can be repositioned by 90°

Data

Ordering data

EAN (European Article Number)	4030661033945
eCl@ss number, Version 9.0	27-27-06-01
eCl@ss number, Version 11.0	27-27-06-01
ETIM number, version 6.0	EC000030
ETIM number, version 7.0	EC000030

Approval - Standards

Certificates	DNV.GL EAC
--------------	---------------

General data

Standards	EN 60947-5-1
Active principle	mechanical
Slide form	Castor
Enclosure material	Grey cast iron, galvanised

Enclosure coating material	painted
Material of the contacts, electrical	Silver
Roller material	Plastic
Gross weight	1,975 g

General data - Features

Number of openers	2
Number of shutters	2

Safety appraisal - Safety outputs

B10d Normally-closed contact (NC)	2,000,000 Operations
-----------------------------------	----------------------

Mechanical data

Actuating element	Roller plunger
Mechanical life, minimum	10,000,000 Operations
Actuating angle, from left of switch axis	30 °
Actuating angle, from right of switch axis	30 °
Contact opening	max. 2 x 6 mm
Actuating speed, minimum	1 mm/min
Actuating speed, maximum	0.5 m/s
Note (Actuating speed)	Actuating speed with vertical actuating angle to switch axis

Mechanical data - Connection technique

Terminal Connector	Screw connection
Cable section, minimum	1.5 mm ²
Cable section, maximum	2.5 mm ²
Note (Cable section)	All indications about the cable section are including the conductor ferrules.
Wire cross-section	13 AWG

Mechanical data - Dimensions

Length of sensor	64 mm
Width of sensor	118 mm
Height of sensor	201 mm
Width of Castor	6.5 mm
Diameter of Castor	25 mm

Ambient conditions

Degree of protection	IP65 to EN 60529
Ambient temperature, minimum	-30 °C
Ambient temperature, maximum	+90 °C

Ambient conditions - Insulation value

Rated insulation voltage U_i	400 V
Rated impulse withstand voltage U_{imp}	6 kV

Electrical data

Thermal test current	16 A
Utilisation category AC-15	400 VAC
Utilisation category AC-15	4 A
Switching element	NO contact / NC contact
Note (Switching element)	with double break
Switching principle	Creep circuit element

Schmersal, Inc., 15 Skyline Drive, Hawthorne, NY 10532

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 11/9/2021, 9:15 AM