DATASHEET





MV3H 330-11Y-RMS-1164

- interlocked shaft and Swivel lever
- with brass roller
- Metal enclosure
- Long life
- 40 mm x 76 mm x 40 mm (basic component)
- Suitable for low actuating speeds
- 1 Cable entry M 20 x 1.5
- free of silicon
- proved in power station applications
- Actuator head can be repositioned in steps 4 x 90°
- Continuous adjustment of lever position 360°
- Lever can be transposed by 180°

Data

Ordering data

EAN (European Article Number) 4030661027975

Approval - Standards

Certificates cULus

CCC

EAC

General data

Standards EN 60947-5-1

Active principle mechanical

Slide form Castor

Enclosure material Light-alloy diecast, paint finish

Enclosure coating material painted

Material of the contacts, electrical Silver

Roller material Plastic

Gross weight 380 g

General data - Features

Number of openers 1

Number of shutters 1

Safety appraisal - Safety outputs

B10d Normally-closed contact (NC) 20,000,000 Operations

Mechanical data

Actuating element Roller lever

Contact opening 2 x 0.5 mm

Actuating speed, minimum 1 mm/min

Actuating torque 0.5 Nm

Repeat accuracy of switching points 0.02

Mechanical data - Connection technique

Terminal Connector Screw connection

Cable section, minimum 1.5 mm²

Cable section, maximum 2.5 mm²

Note (Cable section) All indications about the cable section are including the conductor

ferrules.

Wire cross-section 13 AWG

Mechanical data - Dimensions

Length of sensor 40 mm

Width of sensor 40 mm

Height of sensor 175 mm

Width of Castor 9 mm

Diameter of Castor 37 mm

Ambient conditions

Degree of protection IP65 to EN 60529

Ambient temperature, minimum -30 °C

Ambient temperature, maximum +90 °C

Restistance to shock 50 g / 6 ms

Ambient conditions - Insulation value

Rated impulse withstand voltage U_{imp} 4 kV

Electrical data

Thermal test current 6 A

Utilisation category AC-15 2.5 A

Switching element NO contact, NC contact

Note (Switching element) galvanically separated contact bridges

Schmersal, Inc., 15 Skyline Drive, Hawthorne, NY 10532

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 11/9/2021, 10:57 AM